

## ACCESSORY AIR DRIVE 200 FT-LBS

- ▶ Powered input to a torque multiplier can reduce operator fatigue, increase productivity.
- ▶ Designed to drive Proto® Torque Multipliers (except J6202A).
- ▶ Maximum torque output: 200 ft-lbs (271 Nm).
- ▶ Maximum running air pressure: 60 PSI.
- ▶ Output free speed: 70 RPM.
- ▶ Output rotation: clockwise and counterclockwise.



Product #	Drive Size (in)	Output Drive (in)	Diameter Maximum (in)	Overall Length (in)	Weight (lbs)
<b>J6201</b>	1/2	1/2 Sq. Male	3-1/8	16-1/4	11.00

## AIR DRIVE CONVERTER 200 FT-LBS

- ▶ Powered input to a torque multiplier can reduce operator fatigue, increase productivity.
- ▶ Designed to drive Proto® Torque Multipliers (except J6202A) when used with an air or electric drive tool.
- ▶ Not designed for use with Impact Tools.
- ▶ Maximum torque output: 200 ft-lbs (271 Nm).
- ▶ Maximum torque input: 38 ft-lbs (52 Nm).



Product #	Drive Size (in)	Input Drive (in)	Output Drive (in)	Torque Ratio	Diameter (in)	Overall Length (in)	Weight (lbs)
<b>J6203</b>	1/2	1/2	1/2 Sq. Male	1:5.2	3-1/8	4	5.50

## 3/8" DRIVE 9 PIECE TORQUE ADAPTER SET - 12 POINT

Product #: J5100

Contents	Description
J5112	Torque Adapter 3/8"
J5114	Torque Adapter 7/16"
J5116	Torque Adapter 1/2"
J5118	Torque Adapter 9/16"
J5120	Torque Adapter 5/8"
J5122	Torque Adapter 11/16"
J5124	Torque Adapter 3/4"
J5126	Torque Adapter 13/16"
J5128	Torque Adapter 7/8"


Weight (lbs): 1.32

AS954E S3.8.1

- ▶ Designed for easy torque calibrations.
- ▶ Adapters measure 2" from the center of the square drive to the center of the adapter opening.
- ▶ Special heat-treated alloy steel helps to increase strength and durability.
- ▶ Box end wall thickness is specially engineered to provide strength while still allowing ample room for access to reach difficult fasteners.
- ▶ 12 point box end allows for fine indexing, helping to improve speed and access. Fits 4, 6 and 12 point fasteners.



## 3/8" DRIVE TORQUE ADAPTERS - 12 POINT



Product #	Size (in)	Drive Size (in)	Head Width (in) (B)	Head Depth (in) (C)	Overall Length (in) (L)	Weight (lbs)
<b>J5108</b>	1/4	3/8	13/32	7/32	2-37/64	0.06
<b>J5110</b>	5/16	3/8	31/64	15/64	2-5/8	0.065
<b>J5112</b>	3/8	3/8	9/16	17/64	2-11/16	0.08
<b>J5114</b>	7/16	3/8	21/32	19/64	2-47/64	0.10
<b>J5116</b>	1/2	3/8	47/64	21/64	2-25/32	0.10
<b>J5118</b>	9/16	3/8	13/16	23/64	2-13/16	0.12
<b>J5120</b>	5/8	3/8	29/32	25/64	2-55/64	0.12
<b>J5122</b>	11/16	3/8	1	27/64	2-29/32	0.12
<b>J5124</b>	3/4	3/8	1-5/64	29/64	2-61/64	0.12
<b>J5126</b>	13/16	3/8	1-11/64	31/64	2-63/64	0.14
<b>J5128</b>	7/8	3/8	1-17/64	33/64	3-1/32	0.16

AS954E S3.8.1