

1/2" DRIVE METRIC DEEP LENGTH SOCKETS - 12 POINT

METRIC

- Proto® 12 Point Sockets are ideal for use on stubborn or damaged fasteners, and also on fasteners made from soft materials.
- The TorquePlus™ design is a high performance drive configuration which allows for quick and easy socket engagement to the fastener flats, not the corners.
- The TorquePlus™ configuration employs a radius-corner design, shifting contact area and stress away from the fastener corners and distributing contact stresses over a large area of the socket, minimizing slippage.
- The TorquePlus™ internal design minimizes fastener rounding, helps to extend fastener life, and allows the user to more easily turn worn, rounded, or rusted fasteners.



Product ID No.	mm	B	C	D	E	L	Weight lbs.	ASME Spec.	AS Spec.
J5310M	10 mm	15.4	22.0	15.0	66.5	82.5	0.25 lbs.	ASME B107.5M	AS954E S3.8.1
J5311M	11 mm	18.0	22.0	16.0	66.5	82.5	0.25 lbs.	ASME B107.5M	AS954E S3.8.1
J5312M	12 mm	18.6	22.0	17.0	66.5	82.5	0.26 lbs.	ASME B107.5M	AS954E S3.8.1
J5313M	13 mm	19.2	22.0	17.0	66.5	82.5	0.26 lbs.	ASME B107.5M	AS954E S3.8.1
J5314M	14 mm	21.6	21.6	24.0	66.5	82.5	0.30 lbs.	ASME B107.5M	AS954E S3.8.1
J5315M	15 mm	21.8	21.8	27.0	66.5	82.5	0.32 lbs.	ASME B107.5M	AS954E S3.8.1
J5316M	16 mm	22.0	22.0	30.0	66.5	82.5	0.32 lbs.	ASME B107.5M	AS954E S3.8.1
J5317M	17 mm	24.2	24.2	30.0	66.5	82.5	0.33 lbs.	ASME B107.5M	AS954E S3.8.1
J5318M	18 mm	25.2	25.2	30.0	66.5	82.5	0.33 lbs.	ASME B107.5M	AS954E S3.8.1
J5319M	19 mm	26.7	26.7	30.0	66.5	82.5	0.37 lbs.	ASME B107.5M	AS954E S3.8.1
J5320M	20 mm	27.7	27.7	30.0	66.5	82.5	0.46 lbs.	ASME B107.5M	AS954E S3.8.1
J5321M	21 mm	27.7	27.7	30.0	66.5	82.5	0.51 lbs.	ASME B107.5M	AS954E S3.8.1
J5322M	22 mm	29.7	29.7	30.0	66.5	82.5	0.51 lbs.	ASME B107.5M	AS954E S3.8.1
J5323M	23 mm	30.7	30.7	30.0	66.5	82.5	0.51 lbs.	ASME B107.5M	AS954E S3.8.1
J5324M	24 mm	31.7	31.7	30.0	66.5	82.5	0.51 lbs.	ASME B107.5M	AS954E S3.8.1
J5325M	25 mm	33.2	33.2	30.0	66.5	82.5	0.62 lbs.	ASME B107.5M	AS954E S3.8.1
J5326M	26 mm	33.7	33.7	30.0	66.5	82.5	0.63 lbs.	ASME B107.5M	AS954E S3.8.1
J5327M	27 mm	25.7	25.7	28.0	66.5	82.5	0.65 lbs.	ASME B107.5M	AS954E S3.8.1
J5328M	28 mm	27.7	37.7	28.0	66.5	82.5	0.68 lbs.	ASME B107.5M	AS954E S3.8.1
J5329M	29 mm	37.7	37.6	28.0	66.5	82.5	0.68 lbs.	ASME B107.5M	AS954E S3.8.1
J5330M	30 mm	39.7	39.7	28.0	66.5	82.5	0.70 lbs.	ASME B107.5M	AS954E S3.8.1
J5331M	31 mm	40.7	40.7	28.0	66.5	82.5	0.73 lbs.	ASME B107.5M	AS954E S3.8.1
J5332M	32 mm	40.7	40.7	28.0	66.5	82.5	0.73 lbs.	ASME B107.5M	AS954E S3.8.1
J5336M	36 mm	50.0	50.0	28.0	66.5	82.5	0.99 lbs.	ASME B107.5M	AS954E S3.8.1