



## 1/2" DRIVE CROWFOOT WRENCHES

| INCH    | Product # | Overall Length (in) | Weight (lbs) |
|---------|-----------|---------------------|--------------|
| 15/16   | J5330CF   | 2-13/16             | 0.47         |
| 1       | J5332CF   | 2-13/16             | 0.46         |
| 1-1/16  | J5334CF   | 2-7/8               | 0.51         |
| 1-1/8   | J5336CF   | 3                   | 0.54         |
| 1-3/16  | J5338CF   | 3                   | 0.58         |
| 1-1/4   | J5340CF   | 3-5/16              | 0.66         |
| 1-5/16  | J5342CF   | 3-5/16              | 0.66         |
| 1-3/8   | J5344CF   | 3-3/8               | 0.72         |
| 1-7/16  | J5346CF   | 3-3/8               | 0.75         |
| 1-1/2   | J5348CF   | 3-7/16              | 0.77         |
| 1-9/16  | J5350CF   | 3-1/2               | 0.80         |
| 1-5/8   | J5352CF   | 3-1/2               | 0.83         |
| 1-11/16 | J5354CF   | 3-13/16             | 0.95         |
| 1-3/4   | J5356CF   | 3-13/16             | 0.98         |
| 1-13/16 | J5358CF   | 3-7/8               | 1.01         |
| 1-7/8   | J5360CF   | 3-7/8               | 1.05         |
| 2       | J5364CF   | 3-15/16             | 1.10         |
| 2-1/8   | J5368CF   | 4-1/16              | 1.09         |
| 2-1/4   | J5372CF   | 4-3/8               | 1.27         |
| 2-3/8   | J5376CF   | 4-7/16              | 1.29         |
| 2-7/16  | J5378CF   | 4-7/16              | 1.28         |
| 2-1/2   | J5380CF   | 4-1/2               | 1.25         |

ASME B107.21

- › Crowfoot wrenches are used in hard to reach, restricted access situations where a standard wrench or ratchet cannot reach.
- › Anti-Slip Design open end (ASD).
- › The arched surfaces are designed to spread the contact forces over a greater area and they keep the loads off the corners of the fastener which helps prevent fastener rounding.
- › Broad size range ensures the right tool for the application will be available.
- › Typically used in lower torque applications.
- › Full polish finish provides corrosion resistance and easy to clean surfaces.
- › Locking hole feature helps keep the crowfoot wrench engaged on the extension during use reducing downtime due to detachment of crowfoot in awkward spaces.
- › Use with locking extensions to reach into spaces too small for a mechanic's arm or where the fastener is out of site.



1/2" DRIVE CROWFOOT WRENCHES

## 1/2" DRIVE FLARE NUT CROWFOOT WRENCHES - 12 POINT

- › Designed for speed and safety.
- › Special heat-treated alloy steel helps increase strength and durability.
- › 12 point Box end allows for fine indexing, helping to improve speed and access. Fits 4, 6 and 12 point fasteners.
- › Full polish finish provides corrosion resistance and easy to clean surfaces.

| INCH    | Product # | Overall Length (in) | Weight (lbs) |
|---------|-----------|---------------------|--------------|
| 1-1/8   | J5336FL   | 2-13/16             | 0.19         |
| 1-3/16  | J5338FL   | 2-7/8               | 0.19         |
| 1-1/4   | J5340FL   | 3                   | 0.19         |
| 1-5/16  | J5342FL   | 3-1/16              | 0.19         |
| 1-3/8   | J5344FL   | 3-5/16              | 0.25         |
| 1-7/16  | J5346FL   | 3-3/8               | 0.25         |
| 1-1/2   | J5348FL   | 3-7/16              | 0.25         |
| 1-9/16  | J5350FL   | 3-9/16              | 0.31         |
| 1-5/8   | J5352FL   | 3-3/4               | 0.31         |
| 1-11/16 | J5354FL   | 3-13/16             | 0.31         |
| 1-3/4   | J5356FL   | 3-7/8               | 0.38         |
| 1-13/16 | J5358FL   | 4                   | 0.38         |
| 1-7/8   | J5360FL   | 4-1/4               | 0.45         |
| 1-15/16 | J5362FL   | 4-5/16              | 0.50         |
| 2       | J5364FL   | 4-7/16              | 0.50         |



6 6 POINT  
 8 8 POINT  
 12 12 POINT  
 SPL SPLINE  
 HEX HEX  
 FULL POLISH  
 SATIN  
 BLACK OXIDE  
 INSULATED