

WRENCHES

AEROSPACE ADJUSTABLE WRENCHES

- Wrenches meet and exceed stringent aerospace specification AS4984A which requires tools to have a thicker nickel-chrome coating for greater corrosion-resistance.
- Extra wide jaw capacity.
- Square jaw opening provides strength and tight fit.

| | Maximum Opening (in) | Overall Length (in) | Weight (lbs) |
|-------|----------------------|---------------------|--------------|
| J704A | 1-1/2 | 4-21/64 | 0.15 |
| J706A | 1-31/32 | 6-13/64 | 0.32 |
| J708A | 2-7/16 | 8-7/64 | 0.59 |
| J710A | 2-53/64 | 10-3/64 | 0.99 |
| J712A | 3-17/64 | 12-3/64 | 1.50 |
| J715A | 4-1/4 | 15-1/16 | 2.65 |
| J718A | 4-15/16 | 18-1/8 | 3.75 |

ASME B107.100-2010



CLIK-STOP® ADJUSTABLE WRENCHES

- Satin finish provides corrosion resistance and a slip resistant grip.
- Extra wide jaw capacity.
- Square jaw opening provides strength and tight fit.
- Click-Stop® locking design holds the moving jaw of an adjustable wrench in place when the wrench is in use.

| | | Maximum Opening (in) | Overall Length (in) | Weight (lbs) |
|-------|--------|----------------------|---------------------|--------------|
| J704L | J704SL | 11/16 | 4 | 0.13 |
| J706L | J706SL | 15/16 | 6 | 0.34 |
| J708L | J708SL | 1-1/8 | 8 | 0.57 |
| J710L | J710SL | 1-5/16 | 10 | 0.95 |
| J712L | J712SL | 1-1/2 | 12 | 1.54 |
| J715L | J715SL | 1-11/16 | 15 | 3.13 |
| J718L | J718SL | 2-1/16 | 18 | 5.73 |
| J724L | - | 2-7/16 | 24 | 8.84 |

B107.100-2010



ADJUSTABLE WRENCHES

- Satin finish provides corrosion resistance and a slip resistant grip.
- Extra wide jaw capacity.
- Square jaw opening provides strength and tight fit.
- Rugged I-beam style handle and reinforced stress areas; radius corner design.

| | | Cushion Grip | Maximum Opening (in) | Overall Length (in) | Weight (lbs) |
|------|-------|--------------|----------------------|---------------------|--------------|
| J704 | J704S | J704G | 11/16 | 4 | 0.17 |
| J706 | J706S | J706G | 15/16 | 6 | 0.28 |
| J708 | J708S | J708G | 1-1/8 | 8 | 0.58 |
| J710 | J710S | J710G | 1-5/16 | 10 | 0.90 |
| J712 | J712S | J712G | 1-1/2 | 12 | 1.58 |
| J715 | J715S | - | 1-11/16 | 15 | 3.00 |
| J718 | J718S | - | 2-1/16 | 18 | 4.26 |
| J724 | J724S | - | 2-7/16 | 24 | 6.41 |

ASME B107.100-2010

