

Impact Sockets



3/8" DRIVE EXTENSIONS

- Use extensions to gain access to fasteners in locations that would otherwise be difficult to reach.
- Male square is oriented in line with female squares for use with fixed head torque wrenches.
- Full chamfer at drive opening (when applicable) for easy engagement with drive tools.
- Drive end chamfer and four detents help provide quick positive engagement with drive tool on any of the socket drive walls.



Product ID No.	L	Weight lbs.	ASME Spec.
J7175P	3"	.18	ASME B107.2
J7176P	6"	.35	ASME B107.2
J7178P	12"	.69	ASME B107.2

3/8" DRIVE HAND IMPACT DRIVER

- Designed to loosen hard to turn bolts and screws.
- Heavy-Duty spring for added torque.

Product ID No.	L	Weight lbs.
J7099	5-1/2"	1.66



3/8" DRIVE RETAINING RINGS

- Proto® 3/8" Drive Retaining Rings have a one-piece, without a crush gauge.

Product ID No.	Description	Length	Width	Height	Weight lbs.
JRR37560	Retaining Ring 3/8" Drive 600 GRV	11/16"	11/16"	1/16"	0.01
JRR37567	Retaining Ring 3/8" Drive 670 GRV	3/4"	12/16"	1/16"	0.01
JRR37575	Retaining Ring 3/8" Drive 750 GRV	13/16"	13/16"	1/16"	0.01
JRR37582	Retaining Ring 3/8" Drive 820 GRV	7/8"	7/8"	1/16"	0.01
JRR37595	Retaining Ring 3/8" Drive 950 GRV	1"	1"	1/16"	0.01
JRR37511	Retaining Ring 3/8" Drive 1100 GRV	1-3/16"	1-3/16"	1/16"	0.01
JRR37512	Retaining Ring 3/8" Drive 1200 GRV	1-1/4"	1-1/4"	1/16"	0.01

