IMPACT SOCKETS

1 - 1/2" DRIVE RETAINING RINGS

> Large drive size crush gauge retaining ring.

> Part numbers are embossed on the rings near the point at which the pin and ring meet.



Product #	Description	For Groove Dia. (in)	Diameter (in)	Height (in)	Weight (lbs)
JRR15046	Retaining RIng, CG 1-1/2" DR 2-7/8 Groove	2-7/8	3-3/8	1/4	0.03
JRR15054	Retaining RIng, CG 1-1/2" DR 3-3/8 Groove	3-3/8	3-7/8	1/4	0.03
JRR15062	Retaining RIng, CG 1-1/2" DR 3-7/8 Groove	3-7/8	4-3/8	1/4	0.04
JRR15070	Retaining RIng, CG 1-1/2" DR 4-3/8 Groove	4-3/8	4-7/8	1/4	0.04

HEX HEX

BLACK OXIDE

1 - 1/2" DRIVE IMPACT UNIVERSAL JOINT

- > Tight tolerances for snug fit on fastener.
- > Used wherever powered drive tools are used to install or remove fasteners.
- Designed to withstand the high torque and force associated with impact tools in repetitive application.
 Features two through holes and a groove to accept a Proto[®] Retaining Ring or pin and O-ring to help
- secure the socket to the drive tool anvil.Position at appropriate angle to turn fasteners where obstructions prevent a straight application.
- Ball and spring design which allows for a 30° working angle.
- Smooth 360° rotation.

Product #	Overall Length (in)	Weight (lbs)
J15670A	6-19/64	9.35
		



4 4 POINT 6 6 POINT 8 8 POINT 12 12 POINT SPL SPLINE TORX®