




Wrenches

SET NO. JSCV-20S - 20 PC. REVERSING COMBINATION RATCHETING WRENCH SET - SPLINE

- Black chrome finish is corrosion resistant and visually distinctive.
- Fractional spline wrenches can be used on fractional 4, 6, 12 point, spline fasteners and Torx® fasteners.
- The chrome-vanadium switch lever allows for easy changes in turning direction which helps improve speed.
- 15° angled offset box end helps keep shank clear of obstructions.
- Anti-Slip Design (ASD) open end.
- Patented locking grooves help prevent the wrench from slipping off the fastener when turning.
- The arched surfaces are designed to spread the contact forces over a greater area.
- Loads are kept off the corners of the fastener which helps prevent fastener rounding.
- Weight: 16.20 lbs.



Product ID No.	Contents	 in.	Length
JSCV-20S	JSCV07	7/32"	5"
	JSCV08	1/4"	5"
	JSCV09	9/32"	5-1/2"
	JSCV10	5/16"	5-1/2"
	JSCV11	11/32"	5-15/16"
	JSCV12	3/8"	6-1/4"
	JSCV14	7/16"	6-1/2"
	JSCV16	1/2"	7"
	JSCV18	9/16"	7-1/2"
	JSCV20	5/8"	8-3/16"
	JSCV22	11/16"	8-7/8"
	JSCV24	3/4"	9-3/4"
	JSCV26	13/16"	1-17/16"
	JSCV28	7/8"	1-17/16"
	JSCV30	15/16"	12-3/4"
	JSCV32	1"	12-3/4"
	JSCV34	1-1/16"	14-1/8"
	JSCV36	1-1/8"	15-7/8"
	JSCV40	1-1/4"	16-3/4"
	JSCV48	1-1/2"	19-5/16"
	JSCV20SP	Tool Roll	


Wrenches



REVERSING COMBINATION RATCHETING WRENCHES - SPLINE

- Black chrome finish is corrosion resistant and visually distinctive.
- Fractional spline wrenches can be used on fractional 4, 6, 12 point spline and Torx® fasteners.
- The chrome-vanadium switch lever allows for easy changes in turning direction which helps improve speed.
- 15° angled offset box end helps keep shank clear of obstructions.
- Anti-Slip Design (ASD) open end
- Patented locking grooves help prevent the wrench from slipping off the fastener when turning.
- The arched surfaces are designed to spread the contact forces over a greater area.
- Loads are kept off the corners of the fastener which helps prevent fastener rounding.



Product ID No.	 in.	Length	Width	Height	Weight lbs.
JSCV07	7/32"	5"	9/16"	1/8"	0.06 lbs.
JSCV08	1/4"	5"	9/16"	1/8"	0.06 lbs.
JSCV09	9/32"	5-1/2"	11/16"	1/8"	0.07 lbs.
JSCV10	5/16"	5-1/2"	11/16"	1/8"	0.07 lbs.
JSCV11	11/32"	5-15/16"	3/4"	1/8"	0.09 lbs.
JSCV12	3/8"	6-1/4"	13/16"	1/8"	0.11 lbs.
JSCV14	7/16"	6-1/2"	15/16"	1/8"	0.14 lbs.
JSCV16	1/2"	7"	1-1/16"	3/16"	0.2 lbs.
JSCV18	9/16"	7-1/2"	1-1/8"	3/16"	0.22 lbs.
JSCV20	5/8"	8-3/16"	1-5/16"	3/16"	0.33 lbs.
JSCV22	11/16"	8-7/8"	1-3/8"	3/16"	0.37 lbs.
JSCV24	3/4"	9-3/4"	1-9/16"	1/4"	0.48 lbs.
JSCV26	13/16"	1-17/16"	1-13/16"	1/4"	0.77 lbs.
JSCV28	7/8"	1-17/16"	1-13/16"	1/4"	0.73 lbs.
JSCV30	15/16"	12-3/4"	2-1/16"	1/4"	1.02 lbs.
JSCV32	1"	12-3/4"	2-1/16"	1/4"	1.00 lbs.
JSCV34	1-1/16"	14-1/8"	2-1/4"	5/16"	1.45 lbs.
JSCV36	1-1/8"	15-7/8"	2-5/16"	5/16"	1.96 lbs.
JSCV40	1-1/4"	16-3/4"	2-1/2"	5/16"	2.3 lbs.
JSCV48	1-1/2"	19-5/16"	2-13/16"	3/8"	3.09 lbs.