

TYPE 1 WHEEL EXTENDED RIGHT ANGLE GRINDER

Model Number	H.P.	RPM	Throttle	Spindle	Wheel	O.A.L.	Net Wt.	Housing	Air let
GAL-1340-1	.7	15,500	Safety	3/8"-24 1"Long	4" Type 1	10"	3 1/2 lbs.	Steel	1/4"NPT
GAL-1340A-1	.7	15,500	Safety	3/8"-24 1"Long	4" Type 1	10"	2 3/4 lbs.	Aluminum	1/4"NPT
GAL-1350-1	.7	15,500	Safety lock-off	3/8"-24 1"Long	4" Type 1	10 1/4"	3 3/4 lbs.	Steel	1/4"NPT
GAL-1350A-1	.7	15,500	Safety lock-off	3/8"-24 1"Long	4" Type 1	10 1/4"	3 lbs.	Aluminum	1/4"NPT

***IMPORTANT:** Grinding wheel RPM must exceed tool RPM rating. Never mount bonded grinding wheels. Always wear eye, face, and body protection. Use only reinforced Type 1 wheels, 3" and 4" diameter x 1/4" wide maximum x 3/8" center hole; wheels not included.

Right Angle Collet Grinders

APPLICATIONS

These tools are excellent for applications such as die contouring, deburring, blending and smoothing in hard-to-reach areas. They are used primarily with carbide burrs and mounted points. These tools are used in foundries, refineries, metal fabrication shops, power plants and other industries.

GA-1340-C AND GA-1340A-C

- Rugged 1 HP motor
- 13,500 RPM free speed
- Available in steel or aluminum housing
- Spiral beveled gears for longer life
- Side exhaust with adjustable deflector
- 1/2" side-to-center distance for easy accessibility to work-piece in tight areas
- Interchangeable motor parts with all 1340 and 1350 series grinders
- Interchangeable with CP-3040-LABCID



GA-1340-C



GA-1350-C

GA-1350-C AND GA-1350A-C

- Rugged 1 HP motor
- 13,500 RPM free speed
- Available in steel or aluminum housing
- Spiral beveled gears for longer life
- Side exhaust with adjustable deflector
- Safety lever
- 1/2" side-to-center distance for easy accessibility to work-piece in tight areas
- Interchangeable motor parts with all 1340 and 1350 series grinders
- Interchangeable with CP-3040-GABCID

STANDARD EQUIPMENT

- G-3327 Wrench
- G-3858 Wrench

OPTIONAL EQUIPMENT

- Safety lever
- Safety Lever G-3781 on -1340 style housing

Model Number	H.P.	RPM	Throttle	Spindle	O.A.L.	Net Wt.	Housing	Air let
GA-1340-C	.7	13,500	Safety	1/4" STD	8"	2 3/4 lbs.	Steel	1/4"NPT
GA-1340A-C	.7	13,500	Safety	1/4" STD	8"	2 lbs.	Aluminum	1/4"NPT
GA-1350-C	.7	13,500	Safety lock-off	1/4" STD	8 1/4"	3 lbs.	Steel	1/4"NPT
GA-1350AC	.7	13,500	Safety lock-off	1/4" STD	8 1/4"	2 1/4 lbs.	Aluminum	1/4"NPT

*Specify collet if other than standard 1/4" double angle collet. Optional collet: 1/8", 3/16", 3/8", 23/64"