

Extended Wheel Grinders

APPLICATIONS

These grinders are for weld smoothing, casting clean-up, and burr removal in fabrication shops, die shops, shipyards, power plants, refineries and many other industries.

GE-CONE & PLUG WHEEL GRINDERS

Designed for hard-to-reach surfaces in die construction, castings, and forgings. Also excellent when an extended reach is needed for weld cleaning, deburring, blending and smoothing.

- Heavy duty 1 HP motor
- Available in steel or aluminum housing
- Interchangeable motor parts with all 1340 & 1350 series grinders

GE-1340-20



Model Number	H.P.	RPM	Throttle	Wheel	O.A.L.	Net Wt.	Housing	Air let
GE-1340-20	.9	20,000	Safety	Cone or plug wheel	11"	3 1/4 lbs.	Steel	1/4" NPT
GE-1340A-20	.9	20,000	Safety	Cone or plug wheel	11"	2 1/2 lbs.	Aluminum	1/4" NPT
GE-1350-20	.9	20,000	Safety lock-off	Cone or plug wheel	11 1/4"	3 1/2 lbs.	Steel	1/4" NPT
GE-1350A-20	.9	20,000	Safety lock-off	Cone or plug wheel	11 1/4"	2 3/4 lbs.	Aluminum	1/4" NPT

GE-1340-W & GE-1350-W SERIES

- Heavy duty 1 HP motor, 18,000 RPM
- Extended housing for better reach and control
- Solid steel motor housing ensures longevity
- Interchangeable wheel guards-3" and 4"
- Side exhaust system directs exhaust away from work area
- Motor parts interchangeable with 1340/1350 tools
- GE-1340-W Interchangeable with CP-3040-LANHUT
- GE-1350-W Interchangeable with CP-3040-GANHUT
- GE-1350-W Includes safety lever
- Also available in aluminum housing

GE-1350-W



STANDARD EQUIPMENT

- GE-3939 3" Wheel guard
- G-3327 Wrench
- G-3858 Wrench

OPTIONAL EQUIPMENT

- GE-3781 4" Wheel guard
- G-3781 Safety lever on – 1340 housing

Model Number	H.P.	RPM	Throttle	Wheel	O.A.L.	Net Wt.	Housing	Air let
GE-1340-W	.9	18,000	Safety	3"	12 1/2"	3 3/4 lbs.	Steel	1/4" NPT
GE-1340A-W	.9	18,000	Safety	3"	12 1/2"	3 lbs.	Aluminum	1/4" NPT
GE-1350-W	.9	18,000	Safety lock-off	3"	12 3/4"	4 lbs.	Steel	1/4" NPT
GE-1350A-W	.9	18,000	Safety lock-off	3"	12 3/4"	3 3/4 lbs.	Aluminum	1/4" NP

*Use only reinforced Type 1 wheels. 3" diameter x 1/2" max width x 3/8" center hole; wheels not included. Available in 4" wheel capacity model. When ordering specify 4" wheel with -4, (i.e. GE-1340-4). The -4 model uses only reinforced Type 1 wheels 4" diameter x 1/4" maximum width center hole; wheels not included.