

Right Angle Wheel Grinders

APPLICATIONS

The very popular GA-1340 and GA-1350 style Type 27 wheel tool is now also available in a Type 1 wheel design. The spindle has been lengthened to allow a type 1 wheel with a maximum width of 1/4". For those tight spaces, when cutting or edge grinding is required, the GA-Series Type 1 wheel grinders can meet the challenge. Industrial applications include foundries, welding shops, fabrication plants, steel mills, and shipyards.

GA RIGHT ANGLE SERIES TYPE 27 AND TYPE 1 WHEEL GRINDERS

- Heavy duty 1 HP motor
- 15,500 free speed RPM
- Spiral bevel gears
- Available in steel or aluminum housing
- Side exhaust with adjustable deflector
- Small head for easy accessibility to tight work surfaces
- Motor parts interchangeable with other 1340/1350 tools



GA-1340

GA-1340 & GA-1340-A SERIES

- Interchangeable with CP-3040-LABTIM

GA-1350 SERIES

- Interchangeable with CP-3040-GABTIM
- Safety lever



GA-1350

STANDARD EQUIPMENT TYPE 1

- GA-3500 4" Wheel guard
- GA-3495-1 Wheel spindle nut
- GA-3588-1 Wheel nut
- GA-3652 Spanner wrench
- GA-3653 Wrench
- G-3858 Wrench

STANDARD EQUIPMENT TYPE 27

- GA-3500 4" Wheel guard
- GA-3495 Wheel adapter
- GA-3588 Wheel nut
- GA-3652 Spanner wrench
- GA-3653 Wrench
- G-3858 Wrench

OPTIONAL EQUIPMENT

- GA-3480 3" Guard
- G-3781 Safety lever on – 1340 housing

Model Number	H.P.	RPM	Throttle	Spindle	Wheel	O.A.L.	Net Wt.	Housing	Air let
GA-1340	.7	13,500	Safety	3/8"-24 3/4" Long	4" Type 27	8"	3 1/4 lbs.	Steel	1/4" NPT
GA-1340A	.7	13,500	Safety	3/8"-24 3/4" Long	4" Type 27	8"	2 1/2 lbs.	Aluminum	1/4" NPT
GA-1350	.7	13,500	Safety lock-off	3/8"-24 3/4" Long	4" Type 27	8 1/4"	3 1/2 lbs.	Steel	1/4" NPT
GA-1350A	.7	13,500	Safety lock-off	3/8"-24 3/4" Long	4" Type 27	8 1/4"	2 3/4 lbs.	Aluminum	1/4" NPT

*Use only reinforced Type 27 wheels; 3" or 4" diameter x 1/4" width maximum x 3/8" center hole; wheels not included.