

### Slim Series



Compact at only a 1-3/4" max depth and extremely lightweight, the ProLight™ Slim Line LED Floodlight Series are extremely durable. The units are IP65 rated and suitable for use in all weather conditions. Cool operation enables the Slim Line Series to be used in confined spaces, making it ideal for the Construction, Industrial/MRO, Utilities, Transportation and Environmental channels.

- Pure white light
- Alloy Aluminum body
- IP65 Rated
- No hot surfaces
- 5' integrated power cord
- Multiple mounting options

Model No.	Lumens	Lighting Range	Bulb Type	Lamp Life (hrs)	Features	Kelvins	Watts	Amp Draw	Voltage	Temp Rated	Tested	Cord Type	Weight	IP Rating
411015	1,440	20 ft	LED	50,000	Floor Stand	5,000	15	.25	120	-40°-122°F	cUL	18/3 SJWTW	2.2 lbs	65
411215	1,440	20 ft	LED	50,000	Tripod (311001)	5,000	15	.25	120	-40°-122°F	cUL	18/3 SJWTW	9.7 lbs	65
411315	1,440 x2	30 ft	LED	50,000	Dual Head w/Tripod (311006)	5,000	15 x2	.25 x2	120	-40°-122°F	cUL	18/3 SJWTW	11.9 lbs	65
411030	3,000	35 ft	LED	50,000	Floor Stand	5,000	30	.5	120	-40°-122°F	cUL	18/3 SJWTW	4 lbs	65
411230	3,000	35ft	LED	50,000	Tripod (311006)	5,000	30	.5	120	-40°-122°F	cUL	18/3 SJWTW	11.5 lbs	65
411330	3,000 x2	45 ft	LED	50,000	Dual Head w/Tripod (311006)	5,000	30 x2	.5 x2	120	-40°-122°F	cUL	18/3 SJWTW	15.5 lbs	65
411430	3,000	35 ft	LED	50,000	Magnet Base	5,000	30	.5	120	-40°-122°F	cUL	18/3 SJWTW	6 lbs	65
411050	4,800	50 ft	LED	50,000	Floor Stand	5,000	50	.75	120	-40°-122°F	cUL	18/3 SJWTW	5.4 lbs	65
411250	4,800	50 ft	LED	50,000	Tripod	5,000	50	.75	120	-40°-122°F	cUL	18/3 SJWTW	5.4 lbs	65
411350	4,800 x2	60 ft	LED	50,000	Dual Head w/Tripod (311006)	5,000	50 x2	.75 x2	120	-40°-122°F	cUL	18/3 SJWTW	19.3 lbs	65
411450	4,800	50 ft	LED	50,000	Magnet Base	5,000	50	.75	120	-40°-122°F	cUL	18/3 SJWTW	7.4 lbs	65

### XLE Series



This 50 watt LED work light produces 6,500 lumens due to the extreme energy efficiency and concentrated high-output LEDs utilized. With no hot surfaces, the ProBuilt XLE Series can keep the job site safe and bright while only drawing 1.4 Amps, providing the ultimate energy savings.

Tested and rated to the highest standards, the ProBuilt XLE Series is cUL listed for wet locations and has an IP65 rated housing. Developed for the professional tradesman, the aluminum and steel construction make the ProBuilt XLE Series durable enough for the harshest conditions.

- Sealed on/off switch
- Alloy Aluminum body
- Tempered glass
- No hot surfaces
- 5' integrated power cord
- Multiple mounting options

Model No.	Lumens	Lighting Range	Bulb Type	Lamp Life (hrs)	Features	Kelvins	Watts	Amp Draw	Voltage	Temp Rated	Tested	Cord Type	Weight	IP Rating
111500	6,500	30 ft	LED	50,000	Floor Stand	5,000	50	1.4	120	-30°-120°F	cUL	18/3 SJWTW	9 lbs	65
111505	6,500	30 ft	LED	50,000	Tripod (311006)	5,000	50	1.4	120	-30°-120°F	cUL	18/3 SJWTW	16.5 lbs	65
111507	6,500	30 ft	LED	50,000	Magnet	5,000	50	1.4	120	-30°-120°F	cUL	18/3 SJWTW	11 lbs	65
111000	6,500 x2	60 ft	LED	50,000	Dual Head	5,000	50 x2	1.4 x2	120	-30°-120°F	cUL	18/3 SJWTW	20 lbs	65
111005	6,500 x2	60 ft	LED	50,000	Dual Head w/ Tripod (311007)	5,000	50 x2	1.4 x2	120	-30°-120°F	cUL	18/3 SJWTW	33 lbs	65