

High Bay LED



When the jobsite demands the maximum overhead light output available, ProBuilt's Hang-A-Light® family is just what is needed. All of these lights offer high-output lighting options and include the durability that you expect from a ProBuilt product. No matter how small or large the area, ProBuilt has a light for the job.

- Replaces 400W metal halide with 60% less energy
- 5' Integrated Power Cord
- No Set-Up Required
- Suitable for DAMP Locations

Model No.	Lumens	Lighting Range	Bulb Type	Lamp Life	Kelvins	Watts	Amp Draw	Linking Units	Voltage	Temp Rated	Tested	Cord Type	Weight
111200LED	15,000	75 ft	LED	50,000 hrs	5,000	150	1.6	N/A	120V*	-40° - 125°F	cUL	18/3 SJTW	18 lbs

*Modifiable to 277V

With Receptacle



111060LED 111080LED 1110100LED 1110150LED

Without Receptacle/Plug



111060NR 111080NR 1110100NR




100w / 111900 150w / 111950

- Covered and Protected LED's
- 360° Lighting
- No Hot Surfaces
- Steel Construction
- Welded Wire Safety Cage

Model No.	Lumens	Lighting Range	Bulb Type	Lamp Life	Kelvins	Watts	Amp Draw	Linking Units	Voltage	Temp Rated	Tested	Cord Type	Weight
111060LED	6,500	30 ft	LED	35,000 hrs	5,000	60	0.5	8	120V*	-40° - 125°F	cUL	14/3 SJTW	6.5 lbs
111060NR	6,500	30 ft	LED	35,000 hrs	5,000	60	0.5	N/A	120V*	-40° - 125°F	cUL	14/3 SJTW	6.5 lbs
111080LED	8,600	40 ft	LED	35,000 hrs	5,000	80	0.8	6	120V*	-40° - 125°F	cUL	14/3 SJTW	7 lbs
111080NR	8,600	40 ft	LED	35,000 hrs	5,000	80	0.8	N/A	120V*	-40° - 125°F	cUL	14/3 SJTW	7 lbs
1110100LED	12,000	45 ft	LED	35,000 hrs	5,000	100	0.9	4	120V*	-40° - 125°F	cUL	14/3 SJTW	7.5 lbs
1110100NR	12,000	45 ft	LED	35,000 hrs	5,000	100	0.9	N/A	120V*	-40° - 125°F	cUL	14/3 SJTW	7.5 lbs
1110150LED	16,500	60 ft	LED	35,000 hrs	5,000	150	1.3	3	120V*	-40° - 125°F	cUL	14/3 SJTW	8 lbs

*Modifiable to 277V

Longneck Series



80w / 111980L

- Covered and Protected LED's
- Unique "Longneck" bulb shape
- 5' Integrated Power Cord
- 360° Directional Lighting
- Steel Construction
- Spring Loaded Clamp
- No Hot Surfaces
- Welded Wire Safety Cage

Model No.	Lumens	Lighting Range	Bulb Type	Lamp Life	Kelvins	Watts	Amp Draw	Linking Units	Voltage	Temp Rated	Tested	Cord Type	Weight
111080ECO	7,600	25 ft	LED	25,000 hrs	5,000	80	0.8	6	120V*	-40° - 125°F	cUL	14/3 SJTW	5.35 lbs

*Modifiable to 277V