Pliers, Snips, Clamps & Eye Bolts



RETAINING RING PLIERS - EXTERNAL

- Used with External Retaining Rings.
- Fixed tips are precision formed and induction hardened for accurate fit and long wear.

| Product | Tip | Tip | | Shaft | Weight | ASME |
|---------|-------|------|--------|-----------------|----------|---------|
| ID No. | Angle | Size | Length | Diameter | lbs. | Spec. |
| J391 | 0° | .038 | 6-1/8" | 1/4" - 21/32" | .15 lbs. | B107.19 |
| J397 | 90° | .038 | 6-1/8" | 1/4" - 1" | .15 lbs. | B107.19 |
| J393 | 0° | .070 | 6-7/8" | 7/16" - 2" | .22 lbs. | B107.19 |
| J395 | 0° | .115 | 9-1/8" | 1-1/2" - 3-1/2" | .49 lbs. | B107.19 |

RETAINING RING PLIERS - INTERNAL

- Used with Internal Retaining Rings.
- Fixed tips are precision formed and induction hardened for accurate fit and long wear.

| Product | Tip | Tip | | Weight | ASME |
|--|-----------------------------|--------------------------------------|--|--|--|
| ID No. | Angle | Size | Length | lbs. | Spec. |
| J390 J389 J398 J392 J394 J388 | 0° 0° 45° 0° 0° | .025 .038 .038 .070 .090 | 5-3/8" 5-3/8" 5-3/8" 6-1/2" 9" 5-1/4" | .14 lbs. .13 lbs. .13 lbs. .19 lbs. .47 lbs. | B107.19 B107.19 B107.19 B107.19 B107.19 B107.19 |

