

Pliers, Snips, Clamps & Eye Bolts



RETAINING RING PLIERS - CONVERTIBLE

- Converts from internal to external or vice versa, when pivot screw is moved to adjacent tapped hole.
- Use with either External or Internal Retaining Rings.
- Fixed tips are precision formed and induction hardened for accurate fit and long wear.
- Use the largest diameter tip that will fit the retaining ring being removed or installed.



Product ID No.	Tip Size	Tip Angle	Length	Weight lbs.	ASME Spec.
J399	.038	0°	5-7/8"	.15 lbs.	B107.19
J370	.038	45°	5-3/4"	.16 lbs.	B107.19
J371	.038	90°	5-11/16"	.16 lbs.	B107.19
J372	.047	0°	5-7/8"	.16 lbs.	B107.19
J373	.047	45°	5-3/4"	.15 lbs.	B107.19
J374	.047	90°	5-11/16"	.16 lbs.	B107.19
J385	.070	0°	7-1/2"	.29 lbs.	B107.19
J375	.070	45°	7-3/8"	.32 lbs.	B107.19
J376	.070	90°	7-1/8"	.31 lbs.	B107.19
J377	.090	0°	9-1/4"	.54 lbs.	B107.19
J378	.090	45°	9"	.55 lbs.	B107.19
J379	.090	90°	8-5/8"	.56 lbs.	B107.19
J399L	.038	18°	6"	.19 lbs.	B107.19
J371L	.038	90°	6"	.19 lbs.	B107.19
J385L	.070	18°	7-1/4"	.33 lbs.	B107.19
J376L	.070	90°	7-1/4"	.33 lbs.	B107.19

