

1/4" DRIVE SCREWDRIVER BIT SOCKETS

- › Two piece design allows replacement of worn bits.
- › Bit holders have a hex opening to hold the bit, allowing the bit holder to take the full load of torque.

	Size	Product #	Tip Thickness (in)	Bit Length (in)	Overall Length (in)	Weight (lbs)
Slotted	1/4"	⊖ J4743	3/64	–	1-3/16	0.05
	3/16"	⊖ J4744	1/32	–	1-53/64	0.05
	1/4"	⊖ J4745	3/64	–	1-53/64	0.06
Phillips	#1	⊕ J4737	–	–	1-13/64	0.04
	#2	⊕ J4738	–	–	1-13/64	0.05
Torx®	T10	⊗ J4739-10W	–	5/8	1-1/2	0.06
	T15	⊗ J4739-15W	–	5/8	1-1/2	0.05
	T20	⊗ J4739-20W	–	5/8	1-1/2	0.05
	T25	⊗ J4739-25W	–	5/8	1-1/2	0.05
	T27	⊗ J4739-27W	–	5/8	1-1/2	0.06
	T30	⊗ J4739-30W	–	7/8	1-3/4	0.05



1/4" DRIVE HEX BIT SOCKETS

- › Bit holders have a hex opening to hold the bit allowing the bit holder to take the full load of torque.
- › Made of heat-treated alloy steel.
- › Polished chrome finish.

INCH	HEX	Bit Length (in)	Overall Length (in)	Weight (lbs)
1/16	J47701/16	1	1-7/8	0.05
5/64	J47705/64	1	1-7/8	0.05
3/32	J47703/32	1	1-7/8	0.05
7/64	J47707/64	1	1-7/8	0.06
1/8	J47701/8	1	1-7/8	0.05
9/64	J47709/64	1	1-7/8	0.05
5/32	J47705/32	1	1-7/8	0.05
3/16	J47703/16	1	1-7/8	0.05
7/32	J47707/32	1	1-7/8	0.05
1/4	J47701/4	1	1-7/8	0.06
5/16	J47705/16	1	1-7/8	0.06



1/4" DRIVE BALL END HEX BIT SOCKETS

INCH	HEX	Overall Length (in)	Weight (lbs)
1/4	J47701/4B	1-1/2	0.05
1/8	J47701/8B	1-1/2	0.05
3/16	J47703/16B	1-1/2	0.05
3/32	J47703/32B	1-1/2	0.05
5/32	J47705/32B	1-1/2	0.05
7/32	J47707/32B	1-1/2	0.05
7/64	J47707/64B	1-1/2	0.05
9/64	J47709/64B	1-1/2	0.05



Torx® is a trademark of Acument Intellectual Properties, LLC