

WS 6 SERIES

End Strippers

- For 15 to 46 KV cables
- .900 to 2.030 in. (22.86 to 51.56mm) cable O.D.
- Strips XLPE, polyethylene and EPR insulation*
- Precision stripping with NO conductor damage
- Guarded cutting blade prevents injury
- Rotating stop bar permits accurate preset stripping lengths of up to 2-7/16 in. (61.9 mm). Bar removable for infinite stripping
- WA 1 adapter permits use of SW 2 ratchet wrench
- WA 3 adapter allows strip lengths up to 5-1/2 in. (139.7 mm) and the use of the SW 2 ratchet wrench
- Stop bars with drill adapter can be purchased separately or standard with WS 6DA, inch and metric versions available
- Bushing insert fits over cable
 - Bushing insert presets cutting blade depth
 - Bushings can be changed easily and quickly



- U.S. Patent No.: 3,361,015
- Japan 1,131,678
- Canada 827,962

- Made in the U.S.A.
- Length: 6.5 in. (165 mm)
- Weight: 1.5 lb (680 g)

* See instruction sheet for detailed information



WA 1
wrench adapter
(Part No.: 12920)



WA 3
wrench adapter
(Part No.: 12930)



Ordering Information: Choose tool and bushing (below)

Model	Part No.	Strip Length		Replacement Blade	Rotating Stop Bar
		(inches)	(mm)		
WS 6	12900	1/2 - 2 7/16	12.70 - 61.90	CB 8-2	12928
WS 6 with WA 1	12917	1/2 - 2 7/16	12.70 - 61.90	CB 8-2	12928
WS 6 with WA 3	12918	1/2 - 5 1/2	12.70 - 139.70	CB 8-2	12931
WS 6DA	12950	1/2 - 2 7/16	12.70 - 61.90	CB 8-2	12953
WS 6DA with WA 1	12951	1/2 - 2 7/16	12.70 - 61.90	CB 8-2	12953
WS 6DA with WA 3	12952	1/2 - 5 1/2	12.70 - 139.70	CB 8-2	12954

• CB 8-2 Replacement Blade Part No.: 12903

