

Epoxy



FOR USE ON:

- Steel beams, structural steel & towers
- Concrete floors & conveyors
- Industrial equipment & storage tanks
- Sewage treatment basins
- Non-potable water storage facilities
- Steel handrails



9100 SYSTEM & V9100 SYSTEM DTM EPOXY MASTIC

Versatile epoxy system is perfect for steel beams, rails and concrete floors. A high solids, next generation polyamine converted epoxy.

• *Self-priming, single coat provides service life equal to multiple coats of competitive epoxy*

- Superior long-term solvent, chemical and abrasion resistance
- Outstanding impact resistance
- Convenient 1:1 mixing ratio of base and activator
- Versatile base formula — Works with all activators (Standard, Immersion, Low Temp or Fast Cure) at VOC <340 g/l or <250 g/l
- Meets USDA requirements for incidental food contact

STANDARD ACTIVATOR

- For air and surface temperatures of 50-100°F (10-38°C)

IMMERSION ACTIVATOR

- For fresh or salt water immersion of steel or concrete where water temperatures do not exceed 125°F (52°C)
- Great for use in floor coating applications
- Produces slightly lower gloss than standard activator
- Not for use in potable water tanks

LOW TEMPERATURE ACTIVATOR

- For air and surface temperatures of 40-60°F (5-15°C)

FAST CURE ACTIVATOR

- Faster cure to minimize downtime
- Recoat in 4 hours at 70°F (21°C) and 50% RH
- For air and surface temperature of 50-100°F (10-38°C)
- Produces slightly lower gloss than standard activator

APPLICATION

SUBSTRATE

STEEL

RUSTED STEEL

CONCRETE

MASONRY

VOC g/l

VOC <340

9100

VOC <250

V9100

Covers: 125-225 sq. ft./gal.



This is a two-component system. Order base and activator separately.

COLORS

	9171402 Dunes Tan
	266693 Buff
	9122402 Marlin Blue
	9145402 Equipment Yellow
	9165402 Regal Red
	9168402 Tile Red
	9186402 Navy Gray
	9182402 Silver Gray
	9115402 Aluminum
	9179402 Black
	9192402 White

SAFETY COLORS

	9125402 Safety Blue
	9133402 Safety Green
	9144402 Safety Yellow

Tint Bases also available for custom colors.

Also available in 5-gallon pails.

ACTIVATORS

205015	Standard (<250 g/l)
214430[†]	Immersion (<250 g/l)
9103402	Low Temp. (<250 g/l)
214432	Fast Cure (<250 g/l)

[†] Not for use with Tint Bases

9101402	Standard (<340 g/l)
9102402[†]	Immersion (<340 g/l)
9104402[†]	Fast Cure (<340 g/l)

Coatings

Specialty



FOR USE ON:

- Structural steel & bridges
- Machinery & equipment
- Areas with heavy corrosion
- Tank exteriors, metal roofs & cladding
- Ideal for anywhere that edge coverage is essential and high protection, adhesion, or elasticity is needed.



PEGANOX®

Brush or roller applied, water-based, elastomeric acrylic maintenance coating designed for high protection, adhesion, or elasticity.

- **Utilizes similar technology as Noxyde® but specifically designed to brush and roll**

- Provides excellent long-term corrosion protection
- Reduces project costs with minimal surface preparation
- Ideal for maintenance projects
- Meets USDA requirements for incidental food contact

COLORS

- 225321 White
- 225322 Off White
- 225323 Gray Green
- 225324 Black

APPLICATION

SUBSTRATE

STEEL GALVANIZED

CONCRETE ALUMINUM

VOC g/l

VOC <100
COMPLIANT NATIONWIDE

Covers: 220 sq. ft./gal.



FOR USE ON:

- Industrial machinery & equipment
- Pipes
- Structural steel
- Lockers
- Doors
- Tables



STEEL-TECH® HIGH BUILD EPOXY MASTIC

Epoxy coating that uses 316L stainless steel to protect against corrosion.

- **Fortified with 316L Stainless Steel**

- Applies direct to metal – no primer needed
- For interior and exterior use on steel, concrete and more
- Can be used with 9100 System Activator
- Meets USDA requirements for incidental food contact

COLORS

- 266698 Metallic Gray

ACTIVATORS

- | | | | |
|---------|----------------------|----------|----------------------|
| 205015 | Standard (<250 g/l) | 9101402 | Standard (<340 g/l) |
| 214430† | Immersion (<250 g/l) | 9102402† | Immersion (<340 g/l) |
| 9103402 | Low Temp. (<250 g/l) | 9104402† | Fast Cure (<340 g/l) |
| 214432 | Fast Cure (<250 g/l) | | |

† Not for use with Tint Bases

APPLICATION

SUBSTRATE

STEEL CONCRETE

GALVANIZED RUSTED STEEL

MASONRY

VOC g/l

VOC <250 **VOC <340**

Covers: 125-225 sq. ft./gal.



Floor Coatings



FOR USE ON:

- Steel beams, structural steel & towers
- Concrete floors & conveyors
- Industrial equipment & storage tanks
- Sewage treatment basins
- Non-potable water storage facilities
- Steel handrails

9100 SYSTEM & V9100 SYSTEM DTM EPOXY MASTIC

Versatile, two-component epoxy system is perfect for concrete floors, pools and more. A high solids, next generation polyamine converted epoxy.

• Self-priming, single coat provides service life equal to multiple coats of competitive epoxy

- Superior long-term solvent, chemical and abrasion resistance
- Outstanding impact resistance
- Convenient 1:1 mixing ratio of base and activator
- Versatile base formula — Works with all activators (Standard, Immersion, Low Temp or Fast Cure) at VOC <340 g/l or <250 g/l
- Meets USDA requirements for incidental food contact

STANDARD ACTIVATOR

- For air and surface temperatures of 50-100°F (10-38°C)

IMMERSION ACTIVATOR

- For fresh or salt water immersion of steel or concrete where water temperatures do not exceed 125°F (52°C)
- Great for use in floor coating applications
- Produces slightly lower gloss than standard activator
- Not for use in potable water tanks

LOW TEMPERATURE ACTIVATOR

- For air and surface temperatures of 40-60°F (5-15°C)

FAST CURE ACTIVATOR

- Faster cure to minimize downtime
- Recoat in 4 hours at 70°F (21°C) and 50% RH
- For air and surface temperature of 50-100°F (10-38°C)
- Produces slightly lower gloss than standard activator

APPLICATION

SUBSTRATE

STEEL

RUSTED METAL

CONCRETE

MASONRY

VOC g/l

VOC <340

9100

VOC <250

V9100

Covers: 125-225 sq. ft./gal.



This is a two-component system. Order base and activator separately.

COLORS

	9171402 Dunes Tan
	266693 Buff
	9122402 Marlin Blue
	9145402 Equipment Yellow
	9165402 Regal Red
	9168402 Tile Red
	9186402 Navy Gray
	9182402 Silver Gray
	9115402 Aluminum
	9179402 Black
	9192402 White

SAFETY COLORS

	9125402 Safety Blue
	9133402 Safety Green
	9144402 Safety Yellow

Tint Bases also available for custom colors.

Also available in 5-gallon pails.

ACTIVATORS

9101402	Standard (<340 g/l)
205015	Standard (<250 g/l)
9102402[†]	Immersion (<340 g/l)
214430[†]	Immersion (<250 g/l)
9103402	Low Temp. (<250 g/l)
9104402[†]	Fast Cure (<340 g/l)
214432	Fast Cure (<250 g/l)

[†] Not for use with Tint Bases