

# Coatings

## Epoxy



### FOR USE ON:

- Steel beams & structural steel
- Towers & conveyors
- Industrial equipment & storage tanks
- Sewage treatment basins
- Non-potable water storage facilities
- Steel handrails & floors



## HS9300 SYSTEM EPOXY PRIMER

Maximum protection primers for use with High Performance Epoxy and Topcoats (9100 System DTM Epoxy Mastic, 9800 System DTM Urethane Mastic, 9400 High Gloss Urethane).

### • *Unsurpassed adhesion to metal surfaces and intercoat adhesion*

- Maximum corrosion protection
- Resists heavy abrasion and high moisture exposure
- Can be used on surfaces that reach up to 300°F (149°C)
- Meets USDA requirements for incidental food contact

*This is a two-component system. Order base and activator separately.*


**STANDARD PRIMERS** For recoat times less than 16 hours

	<b>HS9369407</b> Red Primer	<b>ACTIVATOR</b>
	<b>HS9381407</b> Gray Primer	<b>HS9303604</b> Primer Activator





**EXTENDED RECOAT LOW VOC PRIMERS** For recoat times of 16 hours to 30 days— Special order only

	<b>9360402</b> Red Primer	<b>ACTIVATOR</b>
	<b>9370402</b> Buff Primer	<b>9304402</b> Low VOC Primer Activator



**APPLICATION**



**SUBSTRATE**

	
STEEL	GALVANIZED
	
CONCRETE	MASONRY

**VOC g/l**

	
VOC <420 STANDARD	VOC <340

Covers: 590-1175 sq. ft./gal.



## Polyurethane



### FOR USE ON:

- Chemical plants & power plants
- Utilities & vehicles
- Transportation equipment
- Equipment in heavy industrial, severe coastal & offshore environments






## 9700 SYSTEM 250 VOC ACRYLIC POLYESTER URETHANE

This low VOC, high solids, thin film, aliphatic acrylic polyurethane provides the ultimate corrosion protection for excellent long-term appearance in severe environments.

### • *Ultimate color and gloss retention*

- Ultimate corrosion, chemical, impact and abrasion resistance for extreme durability
- Excellent coverage in one coat
- Thin film application (1-2 mils DFT)
- Available accelerator speeds dry time
- Meets USDA requirements for incidental food contact

### COLORS

	<b>207278</b> Silver Gray
	<b>207277</b> Gloss Black
	<b>207279</b> Gloss White
	<b>207273</b> Crystal Clear


### ACTIVATOR

**207243** Activator (qt.)




### COMPANION PRODUCTS

**202548** Urethane Accelerator


**APPLICATION**



**SUBSTRATE**

	
STEEL	GALVANIZED
	
CONCRETE†	

**VOC g/l**


VOC <250

Covers: 360-860 sq. ft./gal.

† May require epoxy primer (see Technical Data Sheet)



*Tint Bases also available for custom colors.*