

# Floor Coatings



#### FOR USE ON:








- Interior and exterior concrete floors
- Walkways
- Decks & patios in mild industrial and commercial environments exposed to heavy and light rubber wheeled traffic

## 5600 SYSTEM ACRYLIC URETHANE FLOOR PAINT


Spruce up your floor with low odor, roll and go floor paint.

- **Protects concrete floors from dusting, water damage and staining**
- Provides a mildew resistant coating
- Use for improved aesthetics, 5S, safety and organization markings and for easy maintenance
- Convenient, ready-to-use with no measuring or mixing
- Excellent coverage over new and previously coated surfaces
- Accepts next day foot traffic
- Meets USDA requirements for incidental food contact


#### COLORS

- |   |                             |   |                             |
|---|-----------------------------|---|-----------------------------|
|  | <b>261117</b> Safety Blue   |  | <b>251286</b> Safety Yellow |
|  | <b>261118</b> Safety Green  |  | <b>251289</b> White         |
|  | <b>261116</b> Safety Orange |  | <b>251291</b> Silver Gray   |
|  | <b>261115</b> Safety Red    |   |                             |

**APPLICATION**



**SUBSTRATE**



WOOD    CONCRETE

**VOC g/l**

**VOC <100**

**COMPLIANT  
NATIONWIDE**

Covers: 170-400 sq. ft./gal.



#### FOR USE ON:

- Floor coating for mild to moderate industrial environments
- Clean rooms, laboratories & schools
- Cafeterias & hospitals







## 6000 SYSTEM WATER-BASED EPOXY

Low VOC, two-component water-based epoxy for industrial floors that features high gloss and is easy to clean.


- **Extended pot life for longer working time**
- Protects against heavy foot traffic and lightweight rubber-wheeled traffic
- Handles occasional mild chemicals, steam, hot water, humidity and moisture
- Cleans with soap and water
- Meets USDA requirements for incidental food contact

Base and activator ordered separately. Combine for 1 gallon activated.


#### COLORS

- |   |                            |   |                      |  |
|---|----------------------------|---|----------------------|--|
|  | <b>6071408</b> Dunes Tan   |  | <b>6092408</b> White | <b>ACTIVATOR</b><br><b>6001604</b> Activator |
|  | <b>6068408</b> Tile Red    |  | <b>6010408</b> Clear |  |
|  | <b>6086408</b> Navy Gray   |   |                      |  |
|  | <b>6082408</b> Silver Gray |   |                      |  |

**APPLICATION**



**SUBSTRATE**



STEEL    CONCRETE

**VOC g/l**

**VOC <250**

Covers: 200-350 sq. ft./gal.

† Prime with Rust-Oleum  
5381405 Gray Primer