

Floor Coatings

Anti-Slip

Preventing slips, trips and falls has never been easier than with Concrete Saver Anti-Slip Floor Coatings. From pedestrian foot traffic in locker rooms to heavy vehicle traffic in warehouses, Concrete Saver products are the easy answer for a safer facility. The coatings are easy to apply with in-house crews and result in a long-lasting durable finish that will protect your floors and the people that walk on them for years to come.



FOR USE ON:

- Interior and exterior concrete floors
- Walkways
- Decks & patios in mild industrial and commercial environments exposed to heavy pedestrian & light rubber wheeled cart traffic



COATING PROFILE

AS5600 SYSTEM ANTI-SLIP FLOOR AND DECK COATING

A fast-drying, tough anti-slip coating to brighten up your floors.


• Ready-to-use with no messy measuring or mixing

- Acrylic formula provides a flexible, low to medium profile, excellent for concrete, asphalt, wood or metal
- Low odor: can be applied during work hours
- Fast drying: can accept foot traffic in as little as 4 hours
- Coefficient of Friction - Dry 1.30, Wet 0.90


COLORS

-  **261175** Safety Yellow
-  **261176** Black
-  **261177** Navy Gray


APPLICATION




SUBSTRATE



CONCRETE



STEEL



WOOD

VOC g/l

VOC <100

COMPLIANT NATIONWIDE

Covers: 60-70 sq. ft./gal.



FOR USE ON:

- Aisles, decks & walkways
- Stairs & machine operating areas
- Entrances & exits



COATING PROFILE






AS5400 SYSTEM ANTI-SLIP ONE-STEP EPOXY

Labor-saving, anti-slip epoxy protects pedestrian grade floors in one step.

• Easy-to-use, single component for fast application

- Ridged profile handles heavy foot traffic and/or light vehicle traffic
- Can be resealed for multi-use areas subjected to mild chemicals, occasional steam and chemical cleaning
- For indoor and outdoor use
- Dries quickly — return to service in 24 hr. for heavy traffic
- Coefficient of friction — Dry: 1.17, Wet: 1.00
- Meets USDA requirements for incidental food contact


COLORS

-  **AS5471402** Dunes Tan
-  **AS5468402** Tile Red
-  **AS5486402** Navy Gray
-  **AS5482402** Silver Gray
-  **AS5479402** Black


SAFETY COLORS

-  **AS5444402** Safety Yellow


APPLICATION




SUBSTRATE



STEEL†



CONCRETE



WOOD

VOC g/l

VOC <340

Covers: 50 sq. ft./gal.

† When primed with 9100 System – DTM Epoxy Mastic