

TPR POWER CORDS

Soft, Bare Copper, TPE Insulated TPR-Black Jacket. (1:5 Extension Ratio)

18 AWG

CATALOG NO.	RETRACTED LENGTHS (INCHES)	NO. OF COND.	AWG NO.	STRAND NO./AWG	U.L. TYPE	MAX. WORKING VOLTAGE	COND. AMP RATING	CABLE O.D. (IN.)	COIL O.D. (IN.)	WT. CORD (LBS.)				
										12"	24"	36"	48"	
SEOW / STOW														
710182	12,24,36,48	10	18	26/30	SEOW / STOW	600	7	0.59	2 3/8	2.3	3.6	5.5	7.1	
72180	12,24,36,48	2	18	41/34	SVEO/STEO	300	7	0.242	7/8	0.35	0.55	0.78	1.01	
72181	12,24,36,48	2	18	41/34	SJEOW/SJTOOW	300	7	0.3	1	0.5	0.76	1.2	1.5	
73181	12,24,36,48	3	18	41/34	SJEOW/SJTOW	300	7	0.308	1 3/8	0.5	0.86	1.25	1.7	
74181	12,24,36,48	4	18	41/34	SJEOW/SJTOW	300	7	0.34	1 3/8	0.65	1.04	1.58	2.06	
75181	12,24,36,48	5	18	41/34	SJEOW/SJTOW	300	7	0.385	1 3/8	0.95	1.51	2.22	3.02	
77182	12,24,36,48	7	18	41/34	SEOW / STOW	600	7	0.5	1-7/8	1.48	2.55	3.76	4.98	

16 AWG

CATALOG NO.	RETRACTED LENGTHS (INCHES)	NO. OF COND.	AWG NO.	STRAND NO./AWG	U.L. TYPE	MAX. WORKING VOLTAGE	COND. AMP RATING	CABLE O.D. (IN.)	COIL O.D. (IN.)	WT. CORD (LBS.)				
										12"	24"	36"	48"	
SJEOW/SJTOW														
73161	12,24,36,48	3	16	65/34	SJEOW/SJTOW	300	10	0.34	1 3/8	0.67	1.15	1.7	2.24	
74161	12,24,36,48	4	16	65/34	SJEOW/SJTOW	300	10	0.365	1 3/8	0.86	1.4	2.02	2.64	
74162	12,24,36,48	4	16	65/34	SEOW/STOW	600	10	0.425	1 1/2	1.2	2.01	2.96	3.9	
76162	12,24,36,48	6	16	65/34	SEOW/STOW	600	10	0.53	2	1.4	2.3	3.3	4.4	
78162	12,24,36,48	8	16	26/30	SEOW / STOW	600	10	0.57	2 1/8	2.3	4.1	5.9	7.9	

14 AWG

CATALOG NO.	RETRACTED LENGTHS (INCHES)	NO. OF COND.	AWG NO.	STRAND NO./AWG	U.L. TYPE	MAX. WORKING VOLTAGE	COND. AMP RATING	CABLE O.D. (IN.)	COIL O.D. (IN.)	WT. CORD (LBS.)				
										12"	24"	36"	48"	
SEOW/ STOW														
73142	12,24,36,48	3	14	41/30	SEOW/ STOW	600	12	0.54	2 1/8	1.82	3.18	4.7	5.8	
74142	12,24,36,48	4	14	41/30	SEOW/STOW	600	12	0.57	2 3/8	1.98	3.42	5.04	6.3	

12 AWG

CATALOG NO.	RETRACTED LENGTHS (INCHES)	NO. OF COND.	AWG NO.	STRAND NO./AWG	U.L. TYPE	MAX. WORKING VOLTAGE	COND. AMP RATING	CABLE O.D. (IN.)	COIL O.D. (IN.)	WT. CORD (LBS.)				
										12"	24"	36"	48"	
SEOW/STOW														
73122	12,24,36,48	3	12	65/30	SEOW/STOW	600	20	0.58	2 3/8	2.2	3.7	5.4	7.3	
74122	12,24,36,48	4	12	65/30	SEOW/STOW	600	20	0.66	2 3/8					