



S39719

25T5/LED/46-850/BP/HO/SE-DE

GENERAL SPECIFICATIONS

Shape:	T5
Wattage:	25W
Color Temperature:	5000K
Length:	46"
Base:	Miniature Bi Pin



TECHNICAL SPECIFICATIONS

Wattage:	25W
Volts:	120V-277V
Fluorescent Equivalent:	54
Shape:	T5
Filament:	LED
Base:	Miniature Bi Pin
ANSI Base:	G5
Finish:	Frosted
Hours Rated:	50000H
Color Temperature:	5000K
CRI:	83CRI

Lumen Output:	3400L
Dimmable:	Non-Dimmable
Beam Spread:	240D
Power Factor:	0.9
Operating Temp:	-25C (-13F) to a maximum of +45C (+113F)
Bypass / Direct:	BallastBypass
Ballast Type:	Type B
Single / Dual End:	Single Ended, Double Ended
Safety Listing:	cULus Classified
Technology:	LED
Material:	Glass

DIMENSIONS

MOL:	46"
MOD:	0.83"
Weight:	0.4

LISTINGS

Safety Listing:	cULus Classified
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PLYF62HN8A9I
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
SDS Class:	LED_Lamp

PACKAGING

Each UPC:	045923397196
Each Quantity:	1
Each Dimensions:	0.83 x 5.20 x 5.20"

Case UPC:	10045923397193
Case Quantity:	25
Case Dimensions:	48.10 x 5.20 x 5.20"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2020
Satco Products, Inc.
All Rights Reserved
November 12, 2020