



**S8892**

13T8/LED/48-840/DUAL/BP-DR

**GENERAL SPECIFICATIONS**

Shape:	T8
Wattage:	13W
Color Temperature:	4000K
Length:	48"
Base:	Medium Bi Pin



**TECHNICAL SPECIFICATIONS**

Wattage:	13W
Volts:	120V-277V
Shape:	T8
Filament:	LED
Base:	Medium Bi Pin
ANSI Base:	G13
Finish:	Frosted
Housing Color:	White
Hours Rated:	50000H
Color Temperature:	4000K
CRI:	83CRI

Lumen Output:	1900L
Dimmable:	Non-Dimmable in Bypass Mode
Beam Spread:	240D
Power Factor:	0.96
Operating Temp:	-20C (-4F) to a maximum of +45C (+113F)
Ballasting Requirements:	Ballast required (Type A) or Ballast Bypass (Type B)
Ballast Type:	Type A/B
Safety Listing:	cULus Listed for Type A; cULus Classified for Type B
Technology:	LED
Material:	Glass

**DIMENSIONS**

MOL:	48"
MOD:	1"

**LISTINGS**

Safety Listing:	cULus Listed for Type A; cULus Classified for Type B
Location Rating:	Damp
Energy Star:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PLIR7BJW4P8T
DLC Primary Use:	Dual Mode Internal Driver (UL Type A and Type B)
UL File Listing:	US&CN E335148; E356817
CEC Terse:	Lawful for sale in California
RoHS Compliant:	Yes
NSF Approved:	Yes - Approved
SDS Class:	LED_Lamp

**PACKAGING**

Each UPC:	045923088926
Each Quantity:	1
Each Dimensions:	48.00 x 1.10 x 1.10"

Case UPC:	10045923088923
Case Quantity:	25
Case Dimensions:	50.20 x 7.30 x 7.30"

110 Heartland Blvd.  
Brentwood, NY 11717  
PH 631-243-2022  
FX 631-243-2027

Distribution Centers  
New York, Florida,  
Texas, Washington,  
California, Puerto Rico

National Toll-Free  
800-43-SATCO  
(800-437-2826)  
www.satco.com

Copyright 2020  
Satco Products, Inc.  
All Rights Reserved  
November 12, 2020