ACCESSORIES & SPECIAL EQUIPMENT

COMPOUND POTS are made of hard rubber that is non-conductive and breakage resistant. The applicator brush and compound are held in one unit that can be hung from aerial devices or fit into cross arm holes. Offered in single and double compartment styles.

CABLE BANDAGES provide temporary insulation for bare conductors and splices. A single thickness of the orange SALCOR® Bandage can withstand 15kV on puncture test. The black neoprene bandage is intended to provide fast and complete temporary cover for cable splicers.

INSULATING SADDLES are ideal for temporary or emergency line work such as stringing light conductors over short spans. The large 3" (76 mm) upper saddle opening will hold bare or insulated conductors in either an upright or inverted position. The IS10 has a voltage rating of 15kV. When necessary to leave energized conductors or jumpers in the saddle for extended periods, it is recommended that they be encased in orange SALCOR® Rib-Grip® line hose. Molded of hard rubber and furnished with two nylon holding pins supplied with steel loops for easy hot-stick application. A 12" (305 mm) orange plastic shoe is affixed to the crossarm opening to help prevent flashover during inclement weather. Designed to fit crossarms with dimensions up to 3.75" x 5" (95 mm x 127 mm).

BELT HOOK/BREAK-AWAY is non-conductive yellow nylon hand-line belt hook that will bend or break if suddenly pulled.

CLIMBER GUARDS are furnished un-slit to accommodate any length, regular or adjustable climbers. Sold in pairs only.

CAT. NO.	DESCRIPTION in. (mm)	WEIGHT EA. lbs. (kgs)
COMPOUND POT S	INGLE COMPARTMENT	
PJB1	1pt. w/ bristle brush, 4.5" x 3.5" (114 x 89)	1.5 (.681)
PJB2	1 pt. w/ wire brush, 4.5" x 3.5 (114 x 114)	1.5 (.681)
CABLE BANDAGES		
414PG	Pure Gum Rubber, 14' (4.3 m) w/o strap	1 (.5)
414BN	Black Neoprene, 14' (4.3 m) w/o strap	1 (.5)
INSULATING SADDI	LE 11.25 x 4.75 (286 x 121)	4 (1.8)
		4 (1.8) .25 (.1)
IS10 ISP BELT HOOK / BREA	11.25 x 4.75 (286 x 121) Replacement Pin K-AWAY	.25 (.1)
IS10 ISP	11.25 x 4.75 (286 x 121) Replacement Pin	. ,
ISP BELT HOOK / BREA	11.25 x 4.75 (286 x 121) Replacement Pin K-AWAY	.25 (.1)







