

## Material Safety Data Sheet

according to ANSI Z400.1- 2004 and 29 CFR 1910.1200



# DRANO® MAX PROFESSIONAL STRENGTH GEL CLOG REMOVER

Version 2.0

Print Date 04/08/2013

Revision Date 08/22/2012

MSDS Number 350000013008

SITE\_FORM Number  
3000000000000010072.002

## 1. PRODUCT AND COMPANY IDENTIFICATION

### Product information

Trade name : DRANO® MAX PROFESSIONAL STRENGTH GEL CLOG REMOVER

Use of the Substance/Mixture : Drain Cleaner  
Company : S.C. Johnson and Son, Limited  
1 Webster Street  
Brantford ON N3T 5R1

Emergency telephone number : 24 Hour Transport & Medical Emergency Phone (866) 231-5406  
24 Hour International Emergency Phone (952) 852-4647  
24 Hour Canadian Transport Emergency Phone (CANUTEC) (613) 996-6666

## 2. HAZARDS IDENTIFICATION

### Emergency Overview

Appearance / Odor : natural colour / gel / Bleach

### Immediate Concerns

: Danger  
Corrosive  
CAUSES EYE AND SKIN BURNS  
HARMFUL OR FATAL IF SWALLOWED.  
Avoid contact with skin, eyes and clothing.  
Avoid breathing vapors, mist or gas.

### Potential Health Effects

Exposure routes : Eye, Skin, Inhalation, Ingestion.

Eyes : Corrosive - causes irreversible eye damage.  
May cause blindness.

Skin : Corrosive to skin  
Causes burns.

Inhalation : Corrosive to respiratory system

Ingestion : Causes severe digestive tract burns.

Aggravated Medical Condition : Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc. may be more susceptible

# Material Safety Data Sheet

according to ANSI Z400.1- 2004 and 29 CFR 1910.1200



## DRANO® MAX PROFESSIONAL STRENGTH GEL CLOG REMOVER

Version 2.0

Print Date 04/08/2013

Revision Date 08/22/2012

MSDS Number 350000013008

SITE\_FORM Number

3000000000000010072.002

to irritating effects

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous chemicals present at or above reportable levels as defined by OSHA 29 CFR 1910.1200 or the Canadian Controlled Products Regulations are listed in this table:

Chemical Name	CAS-No.	Weight percent
Sodium hypochlorite	7681-52-9	5.00 - 10.00
Sodium hydroxide	1310-73-2	1.00 - 5.00
Surfactant - Trade Secret	Mixture	1.00 - 5.00

For additional information on product ingredients, see [www.whatsinsidescjohnson.com](http://www.whatsinsidescjohnson.com).

### 4. FIRST AID MEASURES

- Eye contact : Protect unharmed eye. Remove contact lenses. Flush immediately with plenty of water for at least 15 to 20 minutes. Get medical attention immediately.
- Skin contact : Flush immediately with plenty of water for at least 15 to 20 minutes. Get medical attention immediately. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse.
- Inhalation : Remove to fresh air. If not breathing, give artificial respiration. Get medical attention immediately.
- Ingestion : If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

### 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Specific hazards during firefighting : Container may melt and leak in heat of fire.
- Special protective equipment for firefighters : Wear suitable protective clothing and gloves.
- Further information : Wear full protective clothing and positive pressure self-contained breathing apparatus. In case of fire and/or explosion

## Material Safety Data Sheet

according to ANSI Z400.1- 2004 and 29 CFR 1910.1200



### DRANO® MAX PROFESSIONAL STRENGTH GEL CLOG REMOVER

Version 2.0

Print Date 04/08/2013

Revision Date 08/22/2012

MSDS Number 350000013008

SITE\_FORM Number  
3000000000000010072.002

do not breathe fumes.

Flash point : Note: does not flash

Lower explosion limit : Note: not applicable

Upper explosion limit : Note: not applicable

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear personal protective equipment.

Environmental precautions : Outside of normal use, avoid release to the environment.

Methods for cleaning up : Soak up with inert absorbent material.  
Sweep up and shovel into suitable containers for disposal.  
Dike large spills.  
Clean residue from spill site.

#### 7. HANDLING AND STORAGE

##### Handling

Advice on safe handling : Avoid contact with skin, eyes and clothing.  
Avoid breathing vapors, mist or gas.  
For personal protection see section 8.  
Use only as directed.  
KEEP OUT OF REACH OF CHILDREN AND PETS.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

##### Storage

Requirements for storage areas and containers : Keep in a dry, cool and well-ventilated place.

# Material Safety Data Sheet

according to ANSI Z400.1- 2004 and 29 CFR 1910.1200



## DRANO® MAX PROFESSIONAL STRENGTH GEL CLOG REMOVER

Version 2.0

Print Date 04/08/2013

Revision Date 08/22/2012

MSDS Number 350000013008

SITE\_FORM Number

3000000000000010072.002

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Occupational Exposure Limits

Components	CAS-No.	mg/m3	ppm	Non-standard units	Basis
Sodium hydroxide	1310-73-2	2 mg/m3	-	-	ACGIH Ceiling

#### Personal protective equipment

##### **Respiratory protection**

Use only with adequate ventilation. Substantial amounts of mist/vapors can be controlled with local exhaust ventilation or respiratory protection.

##### **Hand protection**

: Rubber gloves

##### **Eye protection**

Wear splash-resistant Chemical goggles.

##### **Skin and body protection**

: Protective footwear.

##### **Hygiene measures**

: Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: gel
Color	: natural colour
Odor	: Bleach
pH	: 11.5 - 13.5
Boiling point	: 212 °F
Freezing point	: no data available
Flash point	: does not flash
Evaporation rate	: no data available
Auto-ignition temperature	: not applicable

## Material Safety Data Sheet

according to ANSI Z400.1- 2004 and 29 CFR 1910.1200



### DRANO® MAX PROFESSIONAL STRENGTH GEL CLOG REMOVER

Version 2.0

Print Date 04/08/2013

Revision Date 08/22/2012

MSDS Number 350000013008

SITE\_FORM Number  
3000000000000010072.002

Lower explosion limit	:	not applicable
Upper explosion limit	:	not applicable
Vapour pressure	:	no data available
Density	:	1.11 g/cm <sup>3</sup> at 25 °C
Water solubility	:	completely soluble
Partition coefficient: n-octanol/water	:	no data available
Viscosity, dynamic	:	700 cps at 25 °C Method: ASTM D 2196
Volatile Organic Compounds Total VOC (wt. %)*	:	0.1 % - additional exemptions may apply *as defined by US Federal and State Consumer Product Regulations

#### 10. STABILITY AND REACTIVITY

Conditions to avoid	:	Direct sources of heat.
Materials to avoid	:	Do not mix with acids or any other household products. May release dangerous gases (chlorine). Avoid contact with: Ammonia compounds. Rust remover. Strong acids
Hazardous decomposition products	:	Chlorine Sodium oxides No decomposition if used as directed.
Hazardous reactions	:	If accidental mixing occurs and toxic gas is formed, exit area immediately. Do not return until well ventilated.

#### 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity	:	LD50 estimated > 5,000 mg/kg Causes severe digestive tract burns.
---------------------	---	--

## Material Safety Data Sheet

according to ANSI Z400.1- 2004 and 29 CFR 1910.1200



### DRANO® MAX PROFESSIONAL STRENGTH GEL CLOG REMOVER

Version 2.0

Print Date 04/08/2013

Revision Date 08/22/2012

MSDS Number 350000013008

SITE\_FORM Number

30000000000000010072.002

Acute inhalation toxicity : no data available

Acute dermal toxicity : LD50  
estimated  
> 2,000 mg/kg

#### Chronic effects

Carcinogenicity : no data available

Mutagenicity : no data available

Reproductive effects : no data available

Teratogenicity : no data available

Sensitisation : Not known to be a sensitizer.

#### 12. ECOLOGICAL INFORMATION

Ecotoxicity effects : no data available

#### 13. DISPOSAL CONSIDERATIONS

Observe all applicable Federal, Provincial and State regulations and Local/Municipal ordinances regarding disposal.  
Consumer may discard empty container in trash, or recycle where facilities exist.

RCRA waste class : D002 (Corrosive Waste)

#### 14. TRANSPORT INFORMATION

##### Land transport

- U.S. DOT and Canadian TDG Surface Transportation:

# Material Safety Data Sheet

according to ANSI Z400.1- 2004 and 29 CFR 1910.1200



## DRANO® MAX PROFESSIONAL STRENGTH GEL CLOG REMOVER

Version 2.0

Print Date 04/08/2013

Revision Date 08/22/2012

MSDS Number 350000013008

SITE\_FORM Number

3000000000000010072.002

Proper shipping name UN 1760 Corrosive Liquid, N.O.S.  
Class: 8  
UN number 1760  
Packaging group: III  
Note: Limited quantities derogation may be applicable to this product, please check transport documents.

### Sea transport

▪ *IMDG:*  
Proper shipping name UN 1760 Corrosive Liquid, N.O.S.  
Class: 8  
UN number: 1760  
Packaging group: III  
EmS: F-A, S-B  
Note: Limited quantities derogation may be applicable to this product, please check transport documents.

### Air transport

▪ *ICAO/IATA:*  
Proper shipping name UN 1760 Corrosive Liquid, N.O.S.  
Class: 8  
UN/ID No.: UN 1760  
Packaging group: III  
Note: SC Johnson typically does not ship products via air. Refer to IATA/ICAO Dangerous Goods Regulations for detailed instructions when shipping this item by air.

## 15. REGULATORY INFORMATION

Notification status : All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Notification status : All ingredients of this product comply with the New Substances Notification requirements under the Canadian Environmental Protection Act (CEPA).

California Prop. 65 : This product is not subject to the reporting requirements under California's Proposition 65.

Canada Regulations : This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

**Material Safety Data Sheet**

according to ANSI Z400.1- 2004 and 29 CFR 1910.1200



**DRANO® MAX PROFESSIONAL STRENGTH GEL CLOG REMOVER**

Version 2.0

Print Date 04/08/2013

Revision Date 08/22/2012

MSDS Number 350000013008  
SITE\_FORM Number  
30000000000000010072.002

**16. OTHER INFORMATION**

**HMIS Ratings**

<b>Health</b>	3
<b>Flammability</b>	0
<b>Reactivity</b>	0

**NFPA Ratings**

<b>Health</b>	3
<b>Fire</b>	0
<b>Reactivity</b>	0
<b>Special</b>	-

**Further information**

This document has been prepared using data from sources considered to be technically reliable. It does not constitute a warranty, expressed or implied, as to the accuracy of the information contained herein. Actual conditions of use are beyond the seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.

Prepared by:	SC Johnson Global Safety Assessment & Regulatory Affairs (GSARA)
--------------	--