



SPRAY-GLO FLUORESCENT SPRAY PAINT

An ultra high visibility coating for any project that requires a brilliant color. It has 400% greater visibility than regular paint. When topcoated with Seymour's UV resistant Clear coating, it provides exceptional outdoor durability. For best results use Seymour's Hi-Tech White Primer (#16-805) as a base coat. Two coats are recommended followed by a U.V. resistant clear coating of Hi-Tech Gloss Clear Acrylic (#16-121).

Suggested Uses:

Hobby models
Crafts
House numbers
Outdoor equipment
Industrial Identification
Safety Markings
Warning Signs

Benefits:

Greatly increased visibility
VOC compliant
Reduced flammability
Fast drying
Low odor
Easy to apply

Packaging:

Cans per case	6
Shipping weight per case	7 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Flammability	"Flammable"
Flash point	-4F
Specific Gravity	0.80
Solids Content	@26%
VOC content	@61%, cannot exceed 65%
MIR value	@1.02, cannot exceed 1.75
HAPs content	0
Storage Temperature	40-90F
Application Temperature	50-100F
Durability	Good
Abrasion Resistance	Fair
Heat Resistance	250° F
Resin System	V.T. Alkyd
Shelf life	Guaranteed for 2 years
Food contact rating	No

Dry Time*:

To touch 15 minutes

*At 72° F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick coats**

Gloss*: Flat, <15

*as measured on a 60° gloss meter

Available Colors:

Part #	Description	UPC Code
16-1617	Fluorescent Orange	043281001144
16-1618	Fluorescent Red	043281001151
16-1619	Fluorescent Yellow	043281001168
16-1620	Fluorescent Green	043281001175
16-1621	Fluorescent Blue	043281001182