

Product Information Sheet



HI TECH METALLICS AND LACQUERS

A fast drying lacquer based spray paint that provides durable indoor and outdoor protection. Resistant to the effects of weather and many chemicals. Resists abrasion and heat (250F). Bare surfaces or rusted metal surfaces should first be primed with our Hi-Tech primers to ensure proper adhesion.

Suggested Uses:

Home Automotive Industrial Marine Construction

Packaging:

Cans per case

Shipping weight per case

Container Label weight

Shipping Classification

Hazard Class

6

7 lbs.

16 fluid ounce can 12 ounces (340 grams)

Consumer Commodity ORM-D

UN 1950

2.1

Properties:

HAPs content

Flash point -40 F Specific Gravity 0.86

Solids Content Glosses: ~15%

Flats: ~15%

Metallics: ∼13%

MIR value Glosses: ~1.25, cannot exceed 1.40

Clear: ~1.43, cannot exceed 1.50

Metallics: ~1.60, cannot exceed 1.90 Glosses: ~13%

Clear: ~25%

Metallics: ~30%

Storage Temperature 40-100F

Application Temperature 50-90F

Durability Good

Abrasion Resistance Good

Gasoline Resistance No
Heat Resistance 250₀ F

Resin System Acrylic lacquer

Shelf life Guaranteed for 2 years

Dry Time*:

Tack free 5 minutes To recoat 20 minutes

*At 720 F, 50% humidity,

1.5 mil thickness

**Curing/Recoat time is extended with multiple coats and excessively thick

coats**

Gloss*: High Gloss, >80

Semi-Gloss, 10-20

Flat, <15

*as measured on a 600 gloss meter

Available Colors:

Part #	<u>Description</u>	UPC Code	Part #	<u>Description</u>	UPC Code
16-111	Shiny Aluminum	043281000123	16-815	Gloss Black Lacquer	043281001021
16-121	Gloss Clear Acrylic	043281000215	16-821	Gloss Clear Lacquer	043281001038
16-132	Dull Aluminum Metallic	043281000291	16-838	Semi-Gloss Black	043281001069
16-806	Dull Black	043281000987	EN-41	Aluminum	043281003728
16-812	Gold Metallic	043281001007	EN-50	Gold	043281003797
16-813	Gloss White Lacquer	043281001014			

Phone: 815-895-9101 or 800-435-4482

815-895-8475 or 800-343-4258