


Spec 5™ Covers & Gaskets

For O-Z/Gedney Malleable Iron Conduit Bodies



Type BS-S

Type BS-S Domed Top Design Cover

Use:

To cover conduit body opening.

Material/Finish:

Stamped Steel Pre-Galvanized
Stainless Steel Screws
Natural Finish

Third Party Certification:



UL Listed:

E-18095

Suitable for wet locations when used with gaskets, Type SGN or SG on malleable iron conduit bodies.



CSA Certified:

LR-9795

Suitable for wet locations when used with gaskets, Type SGN or SG on malleable iron conduit bodies.


Applicable Third Party Standards:

UL Standard: 514A

CSA Standard: C22.2 No. 18

Fed Spec: A-A-50563

NEMA: FB-1, FB-2.10



Type BC-G

Type BC-G Flat Top Design Cover

Use:

To cover conduit body opening.

Material/Finish:

Gray Iron/Hot Dip Galvanized stainless steel screws.

Third Party Certification:



UL Listed:

E-18095

Suitable for wet locations when used with gaskets, Type SG on malleable iron conduit bodies.



CSA Certified:

LR-9795

Suitable for wet locations when used with gaskets, Type SG on malleable iron conduit bodies.

Applicable Third Party Standards:

UL Standard: 514A

CSA Standard: C22.2 No. 18

Fed Spec: A-A-50563

NEMA: FB-1, FB-2.10



Type SG & SGN

Type SG & SGN Solid Cover Sealing Gasket

Use:

To provide a worry-free, raintight seal when used with Type BS or BC covers.

Material:

Velbuna Composition

Closed-Cell Neoprene Foam Gasket

Temperature Rating: 212°F/100°C

Note: UL/CSA not applicable.

Trade Size (inches)	Catalog Number
1/2	BS-50S
3/4	BS-75S
1	BS-100S
1 1/4-1 1/2	BS-125S
2	BS-200S
2 1/2-3	BS-250S
3 1/2-4	BS-350S*

Trade Size (inches)	Catalog Number
1/2	BC-50G
3/4	BC-75G
1	BC-100G
1 1/4-1 1/2	BC-125G
2	BC-200G
2 1/2-3	BC-250G
3 1/2-4	BC-350G

Trade Size (inches)	Catalog Number Velbuna	Catalog Number Neoprene
1/2	SG-50	SGN-50
3/4	SG-75	SGN-75
1	SG-100	SGN-100
1 1/4-1 1/2	SG-125	SGN-125
2	SG-200	SGN-200
2 1/2-3	SG-250	SGN-250
3 1/2-4	SG-350	SGN-350

* Flat Top Design Cover