

HEAVY DUTY GRADE CLOTH DUCT TAPE

TYPICAL APPLICATIONS

- Seals HVAC ducts
- Metal peening
- Motorsports 200 mph duct tape
- Manufactured housing to seam bottom boards and for patching, seaming and sealing


ADVANTAGES AND BENEFITS

- Waterproof backing
- Excellent holding power
- High tack
- Withstands extreme temperature fluctuations
- Durable
- Co-extruded construction – will not delaminate
- Green Point contributor product

CONSTRUCTION

Overall Grade/Function: Heavy Duty
Backing: Waterproof polyethylene film with a cloth carrier
Adhesive: Natural rubber

COLOR(S)



STANDARD WIDTH(S) STANDARD LENGTH(S)

48 mm 72 mm 55 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	29 lbs/in width	50.8 N/10 mm
Adhesion to Stainless Steel	104 oz/in width	11.38 N/10 mm
Thickness	14 mils	0.35 mm
Elongation	11%	11%
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

Tested in accordance with UL 723; FSI 15/SDI 40; US Green Building Council – LEED[®] Point Contributor Product

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape[®] is a registered trademark of Shurtape Technologies, LLC

Form# TDS-PC-657-12/18/2014