

Catalog Number _____
 Type _____
 Date _____
 Prepared By _____
 Project _____

DLHR and DLHC Emergency Remote Heads



ILLUMINATION Long lasting, efficient ultra-bright white LEDs. High-performance chrome-plated metalized reflector and polycarbonate lens (indoor applications) or glass lens (outdoor applications) for optimal light distribution. Adjustable LED lamp heads increase center-to-center spacing with 8 LEDs in each head.

ELECTRICAL Powered from low voltage power source with low voltage wiring (not provided)

MOUNTING Universal mounting base mounts to single-gang switch box. Distance of maximum run is determined by system voltage, wire

gauge and total maximum wattage on the run. Suitable for wall or ceiling mount.

CONSTRUCTION Indoor application remote heads are injection-molded, engineering-grade, V-0 flame retardant, high-impact, thermoplastic in white or black finish. Outdoor application remote heads are die-case aluminum, sealed and gasketed in gray or black finish.

WARRANTY/LISTING Three year warranty. UL Listed. Meets UL924, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes.

Electrical Information

	Supply Voltage	Max. Watts
DLHR1	3.6V	1.0W
DLHR2	3.6V	2.0W
DLHC1	9.6V	1.0W
DLHC2	9.6V	2.0W

DLHR - For use with DLM and DLP emergency lights with remote capability

DLHC - For use with DLC or SCLB Exit/Emergency combo units with remote capability

DLH Ordering Information

Series	Heads	Color	Options
<u>For SCLB AND DLCRC</u>	1	W = White	WP = Weatherproof
DLHC	2		
<u>For DLMRC AND DLP</u>			
DLHR			