

## SL3310 -- Lithium General Purpose Grease, 14 Wt Oz

**Product Description**

A high purity, NLGI Grade 2 lithium based grease. Provides superior lubrication & durability in any weather and most temperatures. It is a versatile grease designed for light duty applications requiring a long grease life. Will not break down or run out.

**Product Specifications**

<b>Applications</b>	Hinges, latches, overhead door tracks, open gears, chains, cables, slide conveyors, guide rails, cams, pistons, machinery, tools, & equipment. A break-in lubrication for bearings.
<b>Unit Package Description</b>	14 Ounce Cartridge
<b>Brand</b>	Sta-Lube
<b>Generic Description 1</b>	Lithium General Purpose Grease
<b>Net Fill</b>	14 Wt Oz
<b>UPC Code</b>	072213331004
<b>Unit Dimensions</b>	9.31H x 2.13W x 2.13D in
<b>Units Per Case</b>	10
<b>Case Dimensions</b>	9.5H x 4.5W x 11.38D in
<b>Cases Per Pallet</b>	150
<b>Case Weight</b>	11 lbs
<b>I 2 of 5 Code</b>	30072213331005
<b>Appearance</b>	Amber Semi-Solid to Solid Grease
<b>Odor</b>	Petroleum
<b>Base Type</b>	Lithium-12
<b>Flashpoint</b>	450°F
<b>Flammability</b>	Non-flammable
<b>Specific Gravity</b>	0.9 at 60°F
<b>NLGI Grade</b>	2
<b>Timken OK Load [Lbs.]</b>	Not Determined
<b>Plastic Safe</b>	Not Determined
<b>Evaporation Rate</b>	<0.01 (Butyl Acetate=1)
<b>Working Temp</b>	0 to 300°F
<b>4 Ball EP</b>	Not Determined
<b>4 Ball Wear</b>	Not Determined
<b>Drop Point</b>	350°F
<b>Oil Separation</b>	<10%
<b>Oxidation Stability</b>	5
<b>Pour Point</b>	-15°F
<b>ISO Viscosity Grade</b>	150
<b>Water Washout</b>	<15%
<b>Worked Penetration</b>	265 to 295
<b>Propellant</b>	None
<b>NSF Registered</b>	No
<b>DOT Proper Shipping Name</b>	Not Regulated
<b>VOC % (Federal)</b>	<0.1
<b>VOC g/L (Federal)</b>	<0.9
<b>VOC Lbs./Gal. (Federal)</b>	<0.01
<b>VOC Category</b>	Not Regulated
<b>Removal (How To)</b>	Remove with a degreaser or brake cleaner product.