PaintStripe® Floor Marking

BradyID.com/s35



PaintStripe™ Floor Marking Stencil

- Faster application, exact measurement & precise control
- Two adhesive types to securely mask edges and provide easy removal on concrete and other floor surfaces
- Printed cut-lines and a repeating 12-inch ruler facilitate accurate length measurement and rapid alignment of 90° corners

Ideal applications include:

- Areas where paint is preferred for line-marking, such as areas with aggressive or abrasive traffic conditions, or facilities that are unable to use aisle marking tapes due to wet floors, washdown conditions, floor-cleaning protocols or chemical exposures
- Aisle marking, Lean/5S initiatives, fire safety, high-traffic work areas, shipping and receiving docks, and area designation for finished goods, material waste, work-in-progress, raw materials, storage locations and more



Easily installed by one person.



Clean, precise lines.

Lower adhesion (B-518) ideal for clean, polished floors.



Catalog #	Description	Size	Qty
148820	Smooth Flooring	2" Line	100' roll
148808	Smooth Flooring	2" Line	500' roll
148815	Smooth Flooring	2" x 8" Dash	100' roll
148823	Smooth Flooring	2" x 8" Dash	500' roll
148814	Smooth Flooring	3" Line	100' roll
148819	Smooth Flooring	3" Line	500' roll
148806	Smooth Flooring	4" Line	100' roll
148816	Smooth Flooring	4" Line	500' roll

Higher adhesion (B-519) is ideal for dull or worn surfaces.



Catalog #	Description	Size	Qty
148813	Rough Flooring	2" Line	100' roll
148822	Rough Flooring	2" Line	500' roll
148812	Rough Flooring	2" x 8" Dash	100' roll
148818	Rough Flooring	2" x 8" Dash	500' roll
148809	Rough Flooring	3" Line	100' roll
148821	Rough Flooring	3" Line	500' roll
148810	Rough Flooring	4" Line	100' roll
148807	Rough Flooring	4" Line	500' roll

When planning projects, users should test the stencil and paint combination on the intended floor surface.

Try PaintStripe in Your Facility - Contact Brady for a sample!

Paint vs. ToughStripe® Tape

Consider the following attributes of paint and tape to help determine the best fit for your facility.

	Preparation & Execution	Surface	Durability	Environment	Water / Cleaning / Chemical Exposures	Permanency	Multi-Color Lines
Paint	Extensive planning for surface preparation, ventilation and control of ignition or contamination sources. Downtime to allow paint to bond to floor.	Adheres well across many surface types, including rough or pitted floors	Up to 10 years	Suitable for indoor and outdoor use	Better suited for wash down environments and frequent cleaning	Difficult to remove paint completely if the markings need to be rearranged	Difficult to paint two-color or striped lines
Tape	Typically requires less planning and preparation. Tape immediately bonds to floor	Adheres best to smooth surfaces	Up to 3 years	Suitable for indoor, dry environments	Not suitable for frequently wet conditions or liquid chemical exposure	Easier to remove if markings need to be rearranged	Tapes are available in two-color stripes

ToughStripe® Floor Marking

BradyID.com/s35



B-514 Toughstripe Floor Marking Tape

- ToughStripe products are ideal for marking aisles, passageways and storage locations, and pointing out important safety equipment and egress paths
- Exceeds safety standards for clean, dry non-slip surfaces per ANSI A1264.2-2006 and OSHA 1910.22
- 2mm thickness and service temperature range of 0°F – 129°F
- Resists harsh chemicals





	011 1001	011 4001	40.01
	2" x 100'	3" x 100'	4" x 100'
Black	104310	104340	104370
White	104311	104341	104371
Red	104313	104343	104373
Green	104315	104345	104375
Blue	104314	104344	104374
Orange	104316	104346	104376
Yellow	104312	104342	104372
Purple	134086	134087	134088
Brown	134089	134090	134091
Grey	134092	134093	134094
a.o,	10 1002	10 1000	10 100 1

Die-Cut shapes & signs available on the next page!



Striped ToughStripe® Tape

	2" x 100'	3" x 100'	4" x 100'
Org/Blk Striped	132433	132434	132435
Ylw/Blk Striped	104317	104347	104377
Wht/Blk Striped	104319	104349	104379
Rd/Wht Striped	104318	104348	104378
Rd/Ylw Striped	132430	132431	132432
Grn/Wht Striped	132436	132437	132438
Blu/Ylw Striped	132439	132440	132441



Checkered ToughStripe® Tape

	2" x 100'	3" x 100'	4" x 100'
Blk/Wht Checkered	121913	121914	121915
Rd/Wht Checkered	121916	121917	121918



Overlaminate Tape

Catalog #	Description	Size
142134	Overlaminate	1" x 50'
142136	Overlaminate	1.125" x 100'
142135	Overlaminate	2" x 50'
142137	Overlaminate	2.250" x 100'
142138	Overlaminate	3" x 100'
142139	Overlaminate	4" x 100'

ToughStripe® Tape Adhesion Rates

ToughStripe floor tape is easy to apply and remove, yet, it lasts where other factory and warehouse floor marking tapes simply don't.

Silica Crit Garnet Crit Large Diamond Metal

Snall Diamond Metal Heral Heral Heral Heragons Heragonal Metal

Ceranic Tile In Tile Urethane Ceranic Tile Freched Urethane

Low Adhesion

Moderate Adhesion

Strong Adhesion

Questions about your floor type?

We recommend testing a small area before purchasing. To request a free sample, visit BradyID.com/toughstripe.

^{*} For maximum performance, apply ToughStripe Floor Marking products to flat, non-coated concrete.