

Indoor / Outdoor Facility & Safety Labels (B-595)

This low-shrink, continuous vinyl material is pliable with an extremely aggressive adhesive that conforms to smooth or rough surfaces. Ideal for lean 5S labels, pipe markers, equipment and panel labels and production area ID. Vinyl material has 8-10 years average outdoor durability.* These labels offer excellent resistance to oils, detergents, dirt, grime and many solvents.

- **B-595 Indoor/Outdoor Vinyl Material** - Permanent adhesive, very pliable, good for rough surfaces and outdoor use, wide range of colors. Temp. range: -40°F to 180°F (-40°C to 82°C). UL recognized.




Figure 33



Fits Printer Model	Diagram	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Roll Length B Inch (mm)	Labels/Roll	Ribbon in Cartridge
B-595 – Indoor / Outdoor Vinyl Tape									
BMP41, 51, 53	Fig. 33	MC-500-595-WT-BK	B-595	Vinyl	BK on WT	0.500 (12.70)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-750-595-WT-BK	B-595	Vinyl	BK on WT	0.750 (19.10)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-WT-BK	B-595	Vinyl	BK on WT	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP51, 53	Fig. 33	MC-1500-595-WT-BK	B-595	Vinyl	BK on WT	1.500 (38.10)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-YL-BK	B-595	Vinyl	BK on YL	0.500 (12.70)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-750-595-YL-BK	B-595	Vinyl	BK on YL	0.750 (19.10)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-YL-BK	B-595	Vinyl	BK on YL	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP51, 53	Fig. 33	MC-1500-595-YL-BK	B-595	Vinyl	BK on YL	1.500 (38.10)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-OR-BK	B-595	Vinyl	BK on OR	0.500 (12.70)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-750-595-OR-BK	B-595	Vinyl	BK on OR	0.750 (19.10)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-OR-BK	B-595	Vinyl	BK on OR	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP51, 53	Fig. 33	MC-1500-595-OR-BK	B-595	Vinyl	BK on OR	1.500 (38.10)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-BL-WT	B-595	Vinyl	WT on BL	0.500 (12.70)	25 ft. (7.62 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-BL-WT	B-595	Vinyl	WT on BL	0.750 (19.10)	25 ft. (7.62 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-BL-WT	B-595	Vinyl	WT on BL	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R4400
BMP51, 53	Fig. 33	MC-1500-595-BL-WT	B-595	Vinyl	WT on BL	1.500 (38.10)	25 ft. (7.62 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-RD-WT	B-595	Vinyl	WT on RD	0.500 (12.70)	25 ft. (7.62 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-RD-WT	B-595	Vinyl	WT on RD	0.750 (19.10)	25 ft. (7.62 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-RD-WT	B-595	Vinyl	WT on RD	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R4400
BMP51, 53	Fig. 33	MC-1500-595-RD-WT	B-595	Vinyl	WT on RD	1.500 (38.10)	25 ft. (7.62 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-GN-WT	B-595	Vinyl	WT on GN	0.500 (12.70)	25 ft. (7.62 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-GN-WT	B-595	Vinyl	WT on GN	0.750 (19.10)	25 ft. (7.62 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-GN-WT	B-595	Vinyl	WT on GN	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R4400
BMP51, 53	Fig. 33	MC-1500-595-GN-WT	B-595	Vinyl	WT on GN	1.500 (38.10)	25 ft. (7.62 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-WT-RD	B-595	Vinyl	RD on WT	0.500 (12.70)	25 ft. (7.62 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-WT-RD	B-595	Vinyl	RD on WT	0.750 (19.10)	25 ft. (7.62 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-WT-RD	B-595	Vinyl	RD on WT	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R4400
BMP51, 53	Fig. 33	MC-1500-595-WT-RD	B-595	Vinyl	RD on WT	1.500 (38.10)	25 ft. (7.62 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-BK-WT	B-595	Vinyl	WT on BK	0.500 (12.70)	25 ft. (7.62 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-BK-WT	B-595	Vinyl	WT on BK	0.750 (19.10)	25 ft. (7.62 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-BK-WT	B-595	Vinyl	WT on BK	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R4400
BMP51, 53	Fig. 33	MC-1500-595-BK-WT	B-595	Vinyl	WT on BK	1.500 (38.10)	25 ft. (7.62 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-500-595-CL-BK	B-595	Vinyl	BK on CL	0.500 (12.70)	20 ft. (6.09 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-750-595-CL-BK	B-595	Vinyl	BK on CL	0.750 (19.10)	20 ft. (6.09 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-CL-BK	B-595	Vinyl	BK on CL	1.000 (25.40)	20 ft. (6.09 m)	1 roll (cont.)	R6000
BMP51, 53	Fig. 33	MC-1500-595-CL-BK	B-595	Vinyl	BK on CL	1.500 (38.10)	20 ft. (6.09 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-CL-WT	B-595	Vinyl	WT on CL	0.500 (12.70)	20 ft. (6.09 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC-750-595-CL-WT	B-595	Vinyl	WT on CL	0.750 (19.10)	20 ft. (6.09 m)	1 roll (cont.)	R4400
BMP41, 51, 53	Fig. 33	MC1-1000-595-CL-WT	B-595	Vinyl	WT on CL	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R4400
BMP51, 53	Fig. 33	MC-1500-595-CL-WT	B-595	Vinyl	WT on CL	1.500 (38.10)	20 ft. (6.09 m)	1 roll (cont.)	R4400

* Average expected outdoor life of product will depend on user definition of failure, climatic conditions, mounting techniques and material colour. The 8 to 10 year outdoor durability applies to the vinyl label stock only; ribbon durability will vary.

Inside-Panel Component Labels for Electrical, Automation and Data Centers (B-422, B-428, B-483, B-499 and B-595)

Variety of durable materials ideal for marking backer boards, DIN rail, relays, PLCs, switches and solenoids. Create serial or rating plates with barcodes, graphics and more with a flexible high-tack adhesive for easy and long-lasting adhesion.

- B-422 Polyester Material** - Permanent adhesive, good for powder-coated/textured surfaces. Best on flat surfaces. Temp. range: -40°F to 212°F (-40°C to 100°C). UL recognized.
- B-428 Metalized Polyester Material** - Permanent adhesive, silver finish. Temp. range: -40°F to 176°F (-40°C to 80°C). UL recognized.
- B-483 Polyester Material** - Permanent adhesive for powder-coated/textured surfaces. Best on flat surfaces. Temp. range: -40°F to 248°F (-40°C to 120°C). UL recognized.
- B-499 Nylon Cloth Material** - Permanent adhesive. Pliable for rough or smooth surfaces. Temp. range: -94°F to 194°F (-70°C to 90°C). UL recognized.
- B-595 Indoor/Outdoor Vinyl Material** - Permanent adhesive, very pliable, good for rough surfaces and outdoor use, wide range of colors. Temp. range: -40°F to 180°F (-40°C to 82°C). UL recognized.




Figure 29



Figure 33




Figure 46 (with border)

Fits Printer Model	Diagram	Catalog #	B#	Material	Color	Label Width A Inch (mm)	Label Height B Inch (mm)	Labels/Roll	Ribbon in Cartridge
B-422 – Gloss Polyester									
BMP41, 51, 53	Fig. 33	MC-375-422	B-422	Gloss Polyester	BK on WT	0.375 (9.5)	25 ft (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-475-422	B-422	Gloss Polyester	BK on WT	0.475 (12.1)	25 ft (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-422	B-422	Gloss Polyester	BK on WT	0.500 (12.7)	25 ft (7.6 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 29	M-7-422	B-422	Gloss Polyester	BK on WT	0.500 (12.70)	0.500 (12.70)	280	R6000
BMP41, 51, 53	Fig. 29	M-89-422	B-422	Gloss Polyester	BK on WT	0.500 (12.70)	1.500 (38.10)	360	R6000
BMP41, 51, 53	Fig. 29	M-47-422	B-422	Gloss Polyester	BK on WT	1.000 (25.40)	0.500 (12.70)	360	R6000
BMP41, 51, 53	Fig. 29	M-49-422	B-422	Gloss Polyester	BK on WT	1.000 (25.40)	1.000 (25.40)	200	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-422	B-422	Gloss Polyester	BK on WT	1.000 (25.40)	25ft. (7.62m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 29	M-90-422	B-422	Gloss Polyester	BK on WT	1.500 (38.10)	0.750 (19.05)	200	R6000
B-428 – Metalized Polyester									
BMP51, 53	Fig. 29	M-29-428	B-428	Metalized Polyester	Lt. Grey	0.500 (12.70)	1.500 (38.10)	360	R4300
BMP51, 53	Fig. 29	M-30-428	B-428	Metalized Polyester	Lt. Grey	0.750 (19.05)	1.500 (38.10)	260	R4300
BMP41, 51, 53	Fig. 29	M-47-428	B-428	Metalized Polyester	Lt. Grey	1.000 (25.40)	0.500 (12.70)	360	R4300
BMP41, 51, 53	Fig. 46	M-92-428-BB	B-428	Metalized Polyester	Lt. Grey	1.130 (28.70)	0.500 (12.70)	360	R4300
BMP41, 51, 53	Fig. 29	M-60-428	B-428	Metalized Polyester	Lt. Grey	2.000 (50.80)	1.000 (25.40)	80	R4300
B-483 – Ultra Aggressive Polyester									
BMP41, 51, 53	Fig. 29	M-47-483	B-483	Polyester	BK on WT	1.000 (25.4)	0.500 (12.7)	480	R6000
BMP41, 51, 53	Fig. 29	M-61-483	B-483	Polyester	BK on WT	2.000 (50.80)	0.500 (12.70)	80	R6000
BMP41, 51, 53	Fig. 29	M-60-483	B-483	Polyester	BK on WT	2.000 (50.80)	1.000 (25.40)	80	R6000
B-499 – Nylon Cloth									
BMP41, 51, 53	Fig. 29	M-131-499	B-499	Nylon Cloth	BK on WT	0.500 (12.7)	1.000 (25.40)	180	R4300
BMP41, 51, 53	Fig. 29	M-11-499	B-499	Nylon Cloth	BK on WT	0.500 (12.70)	0.750 (19.05)	220	R4300
BMP41, 51, 53	Fig. 29	M-84-499	B-499	Nylon Cloth	BK on WT	0.900 (22.86)	0.500 (12.70)	200	R4300
BMP41, 51, 53	Fig. 29	M-128-499	B-499	Nylon Cloth	BK on WT	1.000 (25.40)	1.900 (48.3)	100	R4300
BMP51, 53	Fig. 29	M-132-499	B-499	Nylon Cloth	BK on WT	1.500 (38.10)	1.250 (31.75)	160	R4300
B-595 – Indoor / Outdoor Vinyl Tape*									
BMP41, 51, 53	Fig. 33	MC-500-595-WT-BK	B-595	Vinyl	BK on WT	0.500 (12.70)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-WT-BK	B-595	Vinyl	BK on WT	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-YL-BK	B-595	Vinyl	BK on YL	0.500 (12.70)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-YL-BK	B-595	Vinyl	BK on YL	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC-500-595-OR-BK	B-595	Vinyl	BK on OR	0.500 (12.70)	25 ft. (7.62 m)	1 roll (cont.)	R6000
BMP41, 51, 53	Fig. 33	MC1-1000-595-OR-BK	B-595	Vinyl	BK on OR	1.000 (25.40)	25 ft. (7.62 m)	1 roll (cont.)	R6000

* For additional vinyl label colors, refer to the B-595 Indoor/Outdoor Grade Facility and Safety Labels on page 326.