



Toll Free: 87 PERMATEX  
(877-376-2839)

10 Columbus Blvd., Hartford,  
Connecticut 06106

6875 Parkland Boulevard, Solon  
Ohio 44139

## Technical Data Sheet

# Permatex<sup>®</sup> Copper Anti-Seize Lubricant

INDUSTRIAL

### PRODUCT DESCRIPTION

S.I.N.: 834-300

Permatex<sup>®</sup> Copper Anti-Seize Lubricant is a high temperature, premium quality copper anti-seize and thread lubricant. It contains a high percentage of micro-fine copper flakes in a semi-synthetic, grease carrier and fortified with high quality rust and corrosion inhibitors. Meets Mil Spec A-907.

### PRODUCT BENEFITS

Permatex<sup>®</sup> Copper Anti-Seize was designed specifically for use on stainless steel or similar alloys. It protects threaded fasteners and fittings from heat, freezing, seizure or galling at temperatures from -30°F to 1800°F. It may be used on pumps, sensors, valves, nuts and bolts where extreme conditions of heat exist. Permatex<sup>®</sup> Copper Anti-Seize also provides good electrical conductivity.

### TYPICAL APPLICATIONS

Threaded assemblies, slide fit assemblies, hinges, gears, chains and sprockets, cables and sheaves, lever pivot points, rollers, oil-still header bolts, furnace equipment threads, tetorts, kilns, ovens, exhaust system bolts and studs, turbine casting studs, marine equipment, mining equipment, farm equipment, heavy equipment, industrial equipment, drawing and forming of metals.

### DIRECTIONS FOR USE

1. Clean mating surfaces before application.
2. For best results, apply to clean, dry surfaces.
3. Clean surfaces with Permatex<sup>®</sup> Brake & Parts Cleaner.
4. Wire brush any loose surface rust.
5. Apply Copper Anti-Seize to the parts that require protection.
6. Reassemble parts using normal torque values.
7. Wipe off excess material.

### For Cleanup

1. Clean parts with disposable towel.
2. Clean hands with Permatex<sup>®</sup> brand hand cleaners.

### PROPERTIES OF MATERIAL

	Typical Value
Chemical Type	Grease
Appearance	Copper metallic paste
Odor	Light petroleum
Specific Gravity	1.2
Temperature Range, °C (°F)	-22(-30) to 982(1800)
Viscosity, cPs	200,000 (base)
Flash Point, °C(°F)	149(300)
NFPA 704 Flammability Rating	1

### GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected for use with chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

### ORDERING INFORMATION

Part Number	Container Size
09126	1 oz. carded tube
31163	16 oz. brush-top bottle
09128	8 oz. brush-top bottle

### STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8\_ to 28\_C (46\_ to 82\_ F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range.

### NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS.

THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.

PLEASE CONTACT PERMATEX, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.  
PERMATEX, INC., HARTFORD SQUARE NORTH, 10 COLUMBUS BOULEVARD, HARTFORD, CT 06106 PHONE - (1-87PERMATEX) Revised 10/02