

Vibra-TITE™ ANTI-SEIZE LUBRICANTS

The Anti-Seize 907 family of lubricants is specially formulated to prevent seizing, galling, pitting, excessive wear, and corrosion. The lubricating formulation is a protective paste consisting of fine flakes of graphite suspended in a blend of lubricants and oils. It will not wash, squeeze or burn out, even at elevated temperatures and high pressures.



NEW Introduction!

**2 ml Bullet Tubes
Multiple Applications
in each Tube!**

Vibra-TITE Part #	Available Sizes	Loctite® Part #	Product Description	Color	Approx. Viscosity (cP)	Temperature Resistance	K-Value	Agency Approvals
907A		Silver	ANTI-SEIZE COMPOUND ALUMINUM					
90702	2 ml bullet	*	Lubricant ideal for all metals to prevent seizing, galling and excessive wear. Resists harsh chemical environments.	Silver	120,000 - 175,000 Paste	1600°F (871°C)	0.18	MIL A-907E GM-6108M
90704	4 oz. brush-top can	80209						
90708	8 oz. brush-top can	76732						
90706	16 oz. brush-top can	76764						
907C		C5-A	ANTI-SEIZE COMPOUND COPPER					
90712	2 ml bullet	*	Lubricant ideal for use on softer metal parts such as copper and brass. Protects from rust and corrosion as well as prevents seizing, galling and excessive wear. Excellent resistance to harsh chemical environments.	Copper	120,000 - 175,000 Paste	1800°F (982°C)	0.16	
90713	3 oz tube	*						
90714	4 oz. brush-top can	51144						
90718	8 oz. brush-top can	51147						
90716	16 oz. brush-top can	51007						
907N		Nickel	ANTI-SEIZE COMPOUND NICKEL					
90722	2 ml bullet	*	Lubricant ideal for extreme temperature copper free base. Resistant to harsh chemical environments. Excellent for stainless steel and other metal fittings.	Silver	500,000 - 350,000 Paste	2400°F (1315°C)	0.13	
90724	4 oz. brush-top can	*						
90728	8 oz. brush-top can	77124						
90726	16 oz. brush-top can	77164						

*Corresponding size not available.

Versatile: Vibra-TITE Anti-Seize 907 is available in four different formulas:

- 1) 907A Aluminum-graphite is a general purpose lubricant. Resists seizing, galling, galvanic attack, and excessive wear.
- 2) 907C Copper-graphite is a general purpose lubricant. Ideal for soft metal parts, plastics and nonmetallic gasketing.
- 3) 907N Nickel-graphite is a high temperature lubricant suitable where different metals (such as brass and steel) come in contact. This product is also available Pre-Applied.

Call: 800-521-2663 or visit: www.threadlockers.com or www.ndindustries.com

Vibra-TITE™ is a trademark of ND Industries, Inc. ©Loctite and Loctite is a registered trademark of the Henkel Corporation

**Vibra-TITE™
GASKETING & LUBRICATING**