



Main

Range of product	Modicon Quantum automation platform
Product or component type	Relay discrete output module
Discrete output number	8
Contacts type and composition	1 NO/NC
Contact form	Form C

Complementary

Discrete output voltage	5...30 V DC 20...250 V AC 30...150 V DC
Addressing requirement	0.5 output word
Maximum load current	2 A 250/30 V AC/DC tungsten 1/4 hp 0,4 3 A 250/30 V AC/DC 5 A 250/30 V AC/DC resistive 60 °C 100 mA 30...50 V DC L/R = 10 ms 300 mA 30...50 V DC resistive
Surge current	≤ 20 A 10 ms capacitive
Switching frequency	30 Hz resistive F = 0.5/l ² L inductive
Switching capacity in VA	1250 VA resistive
Response time on input opening	≤ 10 ms at state 0 to state 1 ≤ 20 ms at state 1 to state 0
Mechanical durability	10000000 cycles
Electrical durability	50000 cycles 500 mA 30...150 V DC resistive 100000 cycles 5 A 30 V DC resistive 100000 cycles 300 mA 30...150 V DC resistive 100000 cycles 100 mA 30...150 V DC L/R = 10 ms 100000 cycles 30...150 V DC interposing relay 200000 cycles 5 A 250 V AC resistive
Output overvoltage protection	Internal by varistor, 275 V
Isolation between channels	1780 Vrms AC for 1 minute 2500 V DC
Isolation between channels and bus	1780 Vrms AC for 1 minute 2500 V DC for 1 minute
Power dissipation	2.75 W + (0.5 x the number of points on)
Marking	CE
Local signalling	1 LED green bus communication is present (Active) 1 LED red external fault detected (F) 8 LEDs green input status
Bus current requirement	560 mA
Module format	Standard
Product weight	0,3 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Product certifications	ABS C-Tick DNV (Det Norske Veritas) FM Class 1 Division 2 GL GOST RINA RMRS
Standards	CSA 22-2 No 142 UL 508
Resistance to electrostatic discharge	4 kV contact IEC 801-2 8 kV on air IEC 801-2
Resistance to electromagnetic fields	10 V/m 80...2000 MHz IEC 801-3
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-40...85 °C
Relative humidity	95 % without condensation
Operating altitude	≤ 5000 m
RoHS EUR conformity date	4Q2009
RoHS EUR status	Will be compliant