

Main

Actuator Type	Diaphragm
Ampere Rating	10A
Application	Used in pneumatic or hydraulic systems on a wide variety of machine and process applications to protect the equipment and control/monitor the system pressure
Approvals	UL Listed File: E12442 CCN NOWT - CSA Certified File: LR26817 Class 3218 02 - CE Marked
Connection Type	0.5 Inch NPT Conduit Entrance
Contact Arrangement	DPDT
Depth	2.63 Inches
Diaphragm	Nitrile (Buna-N)
Differential	1.6 to 8 PSIG
Differential Type	Adjustable
Enclosure Rating	NEMA 4/4X/13
Enclosure Type	Water tight, Dust tight, Oil tight and Corrosion Resistant (Indoor/Outdoor)
Flange Material	Zinc Plated Steel
Height	3.60 Inches
Maximum Allowable Pressure	100 PSIG
Maximum Voltage Rating	600V
Mounting Type	Flange
Number of Poles	2-Pole
Operating Temperature Range	-10 to 185 Degrees F (-23 to 85 Degrees C)
Pressure Connection	0.25 Inch 18 NPTF
Range on Decreasing Pressure	1.0 to 40 PSIG
Terminal Type	Screw Clamp
Type	G
Width	3.50 Inches
Wire Size	#12 to #22 AWG

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.