

Main

Ampere Rating	15A
Approvals	UL Listed File Number E78403 CCN NKCR - CSA Certified File Number LR60905 Class 321103
Coil Voltage	240VAC@60Hz - 220VAC@50Hz
Contact Arrangement	SPDT
Contact Break	15A@120VAC, 10A@240VAC, 6A@480VAC, 5A@600VAC
Contact Configuration	Delayed: 1 N.O./1N.C. - Instantaneous: None
Contact Make	40A@120VAC, 20A@240VAC, 10A@480VAC, 8A@600VAC
Max Operating Temperature	104 Degree F
Maximum Voltage Rating	600VAC
Mounting Type	Panel
Operating Temperature Range	68 to 104 Degree F
Reset Time	On Delay 29ms, Off Delay 27ms average
Terminal Type	Screw Clamp
Timing Mode	On Delay (convertible)
Timing Range	0.1 Second to 1 Minute
Type	A

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.