

Main

| | |
|------------------------|---|
| Ampere Rating | 10A |
| Approvals | UL Listed File Number E78351 CCN NLDX - CSA Certified File Number 214768 Class 321107 - CE Marked |
| Coil Voltage | 120VAC - 110VDC |
| Contact Arrangement | DPDT |
| Contact Break | 3A@120VAC, 1.5A@240VAC |
| Contact Configuration | 2 N.O./2 N.C. |
| Contact Make | 30A@120VAC, 15A@240VAC |
| Features | Up to +/- 0.1 Percentage Repeat Accuracy; Transient Protected; Variable or Fixed Time Delay; Available in 5 timing modes. |
| Horsepower Rating | 1/3HP@120VAC - 1/2HP@240VAC |
| Maximum Voltage Rating | 240VAC |
| Mounting Type | Socket |
| Number of Pins | 11 Pin |
| Timing Mode | Off Delay |
| Timing Range | 0.6 - 60 Minutes |
| Type | JCK |
| Type of Pins | Tubular |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.