

Main

Ampere Rating	10A
Approvals	UL Listed File Number E78351 CCN NLDX - CSA Certified File Number 214768 Class 321107 - CE Marked
Coil Voltage	120VAC - 110VDC
Contact Arrangement	DPDT
Contact Break	3A@120VAC, 1.5A@240VAC
Contact Configuration	2 N.O./2 N.C.
Contact Make	30A@120VAC, 15A@240VAC
Features	Up to +/- 0.1 Percentage Repeat Accuracy; Transient Protected; Variable or Fixed Time Delay; Available in 5 timing modes.
Horsepower Rating	1/3HP@120VAC - 1/2HP@240VAC
Maximum Voltage Rating	240VAC
Mounting Type	Socket
Number of Pins	8 Pin
Timing Mode	Repeat Cycle
Timing Range	1.2 - 120 Minutes
Type	JCK
Type of Pins	Tubular

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.