

EE75S3H

EE 75KVA, 1PH, 240x480-120/240V, 150C,
AL, C2



Main

Depth	24.00 Inches
Enclosure Code	21D
Enclosure Material	Painted Steel
Enclosure Rating	NEMA 2
Enclosure Type	Drip Proof (Indoor)
Full Capacity Taps	(6) 2.5% 2+4-
Height	37.00 Inches
Insulation Temperature	220 Degrees C
Mounting Brackets	Ceiling: CMB364
Mounting Type	Floor - Ceiling with mounting brackets
Phase	1-Phase
Primary	240 x 480VAC
Rating	75kVA
Secondary	120/240VAC
Temperature Rise	150 Degrees C
Weathershield	WS364 (purchase seperately)
Width	30.00 Inches
Winding Material	Aluminum

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.