

H365AWK

SWITCH FUSIBLE HD 600V 400A 3P NEMA12



Main

Commercial Status	Commercialised
Product	Single Throw Safety Switch
Current Rating	400 A
Certifications	UL listed
Enclosure Rating	NEMA 3R/12 galvanized steel
Factory Installed Neutral	None
Disconnect Type	Fusible disconnect
Short Circuit Current Rating	200 kA R, J or L 10 kA H or K
Mounting Type	Surface
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	Heavy duty
Voltage Rating	600 V AC/DC
Wire Size	1/0...750 AWG/kcmil copper or aluminium

RoHS compliance

RoHS EUR status	Will be compliant
RoHS EUR conformity date(YYWW)	3Q2014

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.