



Main

AC Magnetic Trip Setting	350A - 750A Adjustable Trip
Ampere Rating	20A
Approvals	UL Listed - CSA Certified - IEC Rated
Catalog Reference Number	0611CT0401
Circuit Breaker Type	Standard
Depth	4.36 Inches
For Use With	I-Line Panelboards and Switchboards
Frame Type	H-Frame
General Application	Provides overload and short circuit protection
HACR Rated	Yes
Height	6.40 Inches
Marketing Trade Name	Powerpact
Mounting Type	Plug-On
Number of Poles	3-Pole
Phase Connection	ABC
Short Circuit Current Rating	100kA@240VAC - 65kA@480VAC - 25kA@600VAC
Terminal Type	I-Line Connection (ON end) - Lugs (OFF end)
Type	HJ
Voltage Rating	600VAC
Weight	5 Pounds
Width	4.12 Inches
Wire Size	#14-3/0 AWG(Al/Cu)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.