

HU366AWK

SWITCH NONFUSIBLE HD 600V 600A 3P NEMA12



Main

| | |
|------------------------------|---|
| Commercial Status | Commercialised |
| Product | Single Throw Safety Switch |
| Current Rating | 600 A |
| Certifications | UL listed |
| Enclosure Rating | NEMA 3R/12 galvanized steel |
| Factory Installed Neutral | None |
| Disconnect Type | Non-fusible disconnect |
| Short Circuit Current Rating | 200 kA maximum |
| Mounting Type | Surface |
| Number of Poles | 3 |
| Electrical Connection | Lugs |
| Duty Rating | Heavy duty |
| Voltage Rating | 600 V AC/DC |
| Wire Size | 3/0...500 AWG/kcmil copper or aluminium |

RoHS compliance

| | |
|--------------------------------|-------------------|
| RoHS EUR status | Will be compliant |
| RoHS EUR conformity date(YYWW) | 3Q2014 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.