

# Product data sheet

## Characteristics

# LC1D123BL

## contactor TeSys LC1-D - 3 poles - AC-3 440V 12 A - coil 24 V DC



### Main

Range of product	TeSys D
Product or component type	Contactor
Device short name	LC1D
Contactor application	Motor control Resistive load
Utilisation category	AC-1 AC-3
Control circuit type	DC
Coil type	Low consumption
Poles description	3P
Pole contact composition	3 NO
[Ie] rated operational current	12 A ≤ 60 °C AC AC-3 power circuit 16 A ≤ 60 °C AC AC-1 power circuit
Motor power kW	3 kW 220...240 V AC 50/60 Hz 5,5 kW 380...400 V AC 50/60 Hz 5,5 kW 415 V AC 50/60 Hz 5,5 kW 440 V AC 50/60 Hz 7,5 kW 500 V AC 50/60 Hz 7,5 kW 660...690 V AC 50/60 Hz
Motor power hp	1 hp 115 V 1P AC 60 Hz UL 1 hp 115 V 1P AC 60 Hz CSA 2 hp 230/240 V 1P AC 60 Hz UL 2 hp 230/240 V 1P AC 60 Hz CSA 3 hp 230/240 V 3P AC 60 Hz CSA 3 hp 230/240 V 3P AC 60 Hz UL 3 hp 200/208 V 3P AC 60 Hz CSA 3 hp 200/208 V 3P AC 60 Hz UL 7,5 hp 460/480 V 3P AC 60 Hz CSA 7,5 hp 460/480 V 3P AC 60 Hz UL 10 hp 575/600 V 3P AC 60 Hz CSA 10 hp 575/600 V 3P AC 60 Hz UL
Control circuit voltage	24 V DC
Connections - terminals	Spring terminal power circuit 1 2,5 mm <sup>2</sup> flexible without Spring terminal power circuit 2 2,5 mm <sup>2</sup> flexible without Spring terminal control circuit 1 2,5 mm <sup>2</sup> flexible without Spring terminal control circuit 2 2,5 mm <sup>2</sup> flexible without

### Complementary

Coil technology	Built-in bidirectional peak limiting diode suppressor
Protective cover	With
Auxiliary contacts type	Mechanically linked IEC 60947-5-1 1 NO + 1 NC Mirror contact IEC 60947-4-1 1 NC
Auxiliary contact composition	1 NO + 1 NC
Control circuit voltage limits	0.1...0.3 Uc ≤ 60 °C drop-out 0.8...1.25 Uc ≤ 60 °C operational
Time constant	40 ms
[Ui] rated insulation voltage	600 V UL power circuit 600 V CSA power circuit 600 V UL control circuit 600 V CSA control circuit 690 V IEC 60947-1 power circuit 690 V IEC 60947-1 control circuit

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

[Uimp] rated impulse withstand voltage	6 kV IEC 60947
Overvoltage category	III
Mounting support	Plate Rail
Flame retardance	V1 UL 94
[Ue] rated operational voltage	<= 690 V AC 25...400 Hz power circuit
[Ith] conventional free air thermal current	10 A ≤ 60 °C control circuit 16 A ≤ 60 °C power circuit
Irms rated making capacity	250 A 440 V power circuit IEC 60947 250 A DC control circuit IEC 60947-5-1
Rated breaking capacity	250 A 440 V power circuit IEC 60947
Permissible short-time rating	30 A ≤ 40 °C 10 min power circuit 61 A ≤ 40 °C 1 min power circuit 100 A 1 s control circuit 105 A ≤ 40 °C 10 s power circuit 120 A 500 ms control circuit 140 A 100 ms control circuit 210 A ≤ 40 °C 1 s power circuit
Associated fuse rating	10 A gG control circuit IEC 60947-5-1 25 A gG <= 690 V type 2 power circuit 40 A gG <= 690 V type 1 power circuit
Average impedance	2,5 mOhm 50 Hz 16 A power circuit
Power dissipation per pole	0,36 W AC-3 1,56 W AC-1
Inrush power in W	2,4 W 20 °C
Hold-in power consumption in W	5,4 W 20 °C
Operating time	25 ms opening 77 ms closing
Mechanical durability	30000000 cycles
Operating rate	3600 cyc/h ≤ 60 °C
Minimum switching current	5 mA control circuit
Minimum switching voltage	17 V control circuit
Non-overlap time	1,5 ms on de-energisation between NC and NO contacts 1,5 ms on energisation between NC and NO contacts
Insulation resistance	> 10 MOhm control circuit
Rated operational power in W	14 W 24 V DC-13 10000000 cycles control circuit 48 W 24 V DC-13 3000000 cycles control circuit 96 W 24 V DC-13 1000000 cycles control circuit
Height	99 mm
Width	45 mm
Depth	93 mm 95 mm
Product weight	0,485 kg

## Environment

Standards	CSA C22-2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508
Product certifications	BV CCC CSA DNV (Det Norske Veritas) GL GOST LROS RINA UL
IP degree of protection	IP2x VDE 0106 IP2x IEC 60529
Protective treatment	TH IEC 60068 3
Ambient air temperature for operation	-5...60 °C
Ambient air temperature for storage	-60...80 °C

Permissible ambient air temperature around the device	-40...70 °C at Uc
Operating altitude	3000 m without
Fire resistance	850 °C IEC 60695-2-1
Shock resistance	10 gn contactor opened 15 gn contactor closed
Vibration resistance	2 gn contactor opened 5...300 Hz 4 gn contactor closed 5...300 Hz
RoHS EUR conformity date	0721
RoHS EUR status	Compliant