

LC2D115G7

reversing contactor TeSys LC2-D - 3 poles -
AC-3 440V 115 A - coil 120 V AC



Main

Range of product	TeSys D
Product or component type	Reversing contactor
Device short name	LC2D
Contact application	Motor control
Utilisation category	AC-2 AC-3 AC-4
Control circuit type	AC
Coil type	Standard
Poles description	3P
Pole contact composition	3 NO
[Ie] rated operational current	115 A \leq 60 °C AC AC-3 power circuit
Motor power kW	30 kW 220...240 V AC 50/60 Hz 55 kW 380...400 V AC 50/60 Hz 59 kW 415 V AC 50/60 Hz 59 kW 440 V AC 50/60 Hz 65 kW 1000 V AC 50/60 Hz 75 kW 500 V AC 50/60 Hz 80 kW 660...690 V AC 50/60 Hz
Control circuit voltage	120 V AC 50/60 Hz
Connections - terminals	Screwclamp terminal power circuit 1 10...120 mm ² flexible without Screwclamp terminal power circuit 1 10...120 mm ² flexible with Screwclamp terminal power circuit 1 10...50 mm ² flexible without Screwclamp terminal power circuit 1 10...50 mm ² flexible with Screwclamp terminal power circuit 1 10...120 mm ² solid without Screwclamp terminal power circuit 1 10...50 mm ² solid without Screwclamp terminal control circuit 1 1...2,5 mm ² flexible without Screwclamp terminal control circuit 2 1...2,5 mm ² flexible without Screwclamp terminal control circuit 1 1...2,5 mm ² flexible with Screwclamp terminal control circuit 2 1...2,5 mm ² flexible with Screwclamp terminal control circuit 1 1...2,5 mm ² solid without Screwclamp terminal control circuit 2 1...2,5 mm ² solid without

Complementary

Assembly style	Ready assembled
Coil technology	Without built-in bidirectional peak limiting diode suppressor
Protective cover	With
Auxiliary contacts type	Mechanically linked IEC 60947-5-1 1 NO + 1 NC Mirror contact IEC 60947-4-1 1 NC
Auxiliary contact composition	1 NO + 1 NC
Interlocking type	Electrical Mechanical

Control circuit voltage limits	0.3...0.5 U _c 55 °C drop-out 50/60 Hz 0.3...0.5 U _c 55 °C drop-out 50/60 Hz 0.8...1.15 U _c 55 °C operational 50/60 Hz 0.85...1.1 U _c 55 °C operational 50/60 Hz
[U _i] rated insulation voltage	600 V UL power circuit 600 V CSA power circuit 600 V UL control circuit 600 V CSA control circuit 690 V IEC 60947-1 control circuit 1000 V IEC 60947-1 power circuit
[U _{imp}] rated impulse withstand voltage	8 kV IEC 60947
Overvoltage category	III
Mounting support	Plate Rail
Flame retardance	V1 UL 94
Tightening torque	1,2 N.m control circuit screwclamp terminal 1...2,5 mm ² Philips No 2 2 mm 1,2 N.m control circuit screwclamp terminal 1...2,5 mm ² flat Ø 6 mm 12 N.m power circuit 2 entry connector 10...120 mm ² hexagonal 4 mm 12 N.m power circuit 2 entry connector 10...50 mm ² hexagonal 4 mm
[U _e] rated operational voltage	<= 1000 V AC 25...400 Hz power circuit
[I _{th}] conventional free air thermal current	10 A ≤ 60 °C control circuit 200 A ≤ 60 °C power circuit
I _{rms} rated making capacity	140 A AC control circuit IEC 60947-5-1 1260 A 440 V power circuit IEC 60947
Rated breaking capacity	1100 A 440 V power circuit IEC 60947
Permissible short-time rating	100 A ≤ 40 °C 10 min power circuit 120 A 1 s control circuit 140 A 500 ms control circuit 250 A ≤ 40 °C 1 min power circuit 550 A ≤ 40 °C 10 s power circuit 950 A ≤ 40 °C 1 s power circuit 1100 A 100 ms control circuit
Associated fuse rating	10 A gG control circuit IEC 60947-5-1 200 A gG <= 690 V type 2 power circuit 250 A gG <= 690 V type 1 power circuit
Average impedance	0,6 mOhm 50 Hz 200 A power circuit
Power dissipation per pole	7,9 W AC-3 200 A
Inrush power in VA	280...350 VA 20 °C 0,8 50 Hz 280...350 VA 20 °C 0,8 60 Hz 300 VA 20 °C 0,8 50 Hz 300 VA 20 °C 0,8 60 Hz
Hold-in power consumption in VA	2...18 VA 20 °C 0,3 60 Hz 2...18 VA 20 °C 0,3 50 Hz 22 VA 20 °C 0,3 50 Hz 22 VA 20 °C 0,3 60 Hz
Operating time	6...20 ms opening 20...50 ms closing
Mechanical durability	8000000 cycles
Operating rate	2400 cyc/h ≤ 60 °C
Minimum switching current	5 mA control circuit
Minimum switching voltage	17 V control circuit
Non-overlap time	1,5 ms on energisation between NC and NO contacts 1,5 ms on de-energisation between NC and NO contacts
Insulation resistance	> 10 MOhm control circuit
Height	158 mm
Width	266 mm
Depth	148 mm
Product weight	6,35 kg

Environment

Standards	CSA C22-2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508
Product certifications	BV CCC CSA DNV (Det Norske Veritas) GL GOST LROS RINA UL
IP degree of protection	IP2x VDE 0106 IP2x IEC 60529
Protective treatment	TH IEC 60068 3
Ambient air temperature for operation	-5...60 °C
Ambient air temperature for storage	-60...80 °C
Permissible ambient air temperature around the device	-40...70 °C at U _c
Operating altitude	3000 m without
Fire resistance	850 °C IEC 60695-2-1
Shock resistance	6 gn contactor opened 15 gn contactor closed
Vibration resistance	2 gn contactor opened 5...300 Hz 4 gn contactor closed 5...300 Hz
Heat dissipation	3...8 W 50/60 Hz control circuit
RoHS EUR conformity date	2Q2009
RoHS EUR status	Will be compliant