

LC2D40G7

reversing contactor TeSys LC2-D - 3 poles -
AC-3 440V 40 A - coil 120 V AC



Main

Range of product	TeSys D
Product or component type	Reversing contactor
Device short name	LC2D
Contactur application	Motor control
Utilisation category	AC-2 AC-3 AC-4
Control circuit type	AC
Coil type	Standard
Poles description	3P
Pole contact composition	3 NO
[Ie] rated operational current	40 A ≤ 60 °C AC AC-3 power circuit
Motor power kW	11 kW 220...240 V AC 50/60 Hz 18,5 kW 380...400 V AC 50/60 Hz 22 kW 415 V AC 50/60 Hz 22 kW 440 V AC 50/60 Hz 22 kW 500 V AC 50/60 Hz 30 kW 660...690 V AC 50/60 Hz
Control circuit voltage	120 V AC 50/60 Hz
Connections - terminals	Screwclamp terminal power circuit 2 1...25 mm ² solid without Screwclamp terminal power circuit 1 1...35 mm ² flexible without Screwclamp terminal power circuit 2 1...35 mm ² flexible without Screwclamp terminal power circuit 1 1...35 mm ² flexible with Screwclamp terminal power circuit 1 1...35 mm ² solid without Screwclamp terminal power circuit 2 1...25 mm ² flexible with Screwclamp terminal power circuit 2 1...35 mm ² flexible with Screwclamp terminal power circuit 2 1...25 mm ² flexible without Screwclamp terminal power circuit 2 1...35 mm ² solid without Screwclamp terminal control circuit 1 1...4 mm ² flexible without Screwclamp terminal control circuit 2 1...4 mm ² flexible without Screwclamp terminal control circuit 1 1...4 mm ² flexible with Screwclamp terminal control circuit 2 1...2,5 mm ² flexible with Screwclamp terminal control circuit 1 1...4 mm ² solid without Screwclamp terminal control circuit 2 1...4 mm ² solid without

Complementary

Assembly style	Ready assembled
Coil technology	Without built-in bidirectional peak limiting diode suppressor
Protective cover	With
Auxiliary contacts type	Mechanically linked IEC 60947-5-1 1 NO + 1 NC Mirror contact IEC 60947-4-1 1 NC

Auxiliary contact composition	1 NO + 1 NC
Interlocking type	Mechanical
Control circuit voltage limits	0.3...0.6 U _c 60 °C drop-out 50/60 Hz 0.8...1.1 U _c 60 °C operational 50 Hz 0.85...1.1 U _c 60 °C operational 60 Hz
[U _i] rated insulation voltage	600 V UL power circuit 600 V CSA power circuit 600 V UL control circuit 600 V CSA control circuit 690 V IEC 60947-1 power circuit 690 V IEC 60947-1 control circuit
[U _{imp}] rated impulse withstand voltage	6 kV IEC 60947
Overvoltage category	III
Mounting support	Plate Rail
Flame retardance	V1 UL 94
Tightening torque	1,7 N.m control circuit screwclamp terminal 1...4 mm ² flat Ø 6 mm 1,7 N.m control circuit screwclamp terminal 1...4 mm ² Philips No 2 2 mm 1,7 N.m control circuit screwclamp terminal 1...2,5 mm ² flat Ø 6 mm 1,7 N.m control circuit screwclamp terminal 1...2,5 mm ² Philips No 2 2 mm 5 N.m power circuit screwclamp terminal 1...25 mm ² hexagonal 4 mm 8 N.m power circuit screwclamp terminal 1...35 mm ² hexagonal 4 mm
[U _e] rated operational voltage	<= 1000 V AC 25...400 Hz power circuit
[I _{th}] conventional free air thermal current	10 A ≤ 60 °C control circuit 60 A ≤ 60 °C power circuit
I _{rms} rated making capacity	140 A AC control circuit IEC 60947-5-1 800 A 440 V power circuit IEC 60947
Rated breaking capacity	800 A 440 V power circuit IEC 60947
Permissible short-time rating	72 A ≤ 40 °C 10 min power circuit 100 A 1 s control circuit 120 A 500 ms control circuit 140 A 100 ms control circuit 165 A ≤ 40 °C 1 min power circuit 320 A ≤ 40 °C 10 s power circuit 720 A ≤ 40 °C 1 s power circuit
Associated fuse rating	10 A gG control circuit IEC 60947-5-1 80 A gG <= 690 V type 1 power circuit 80 A gG <= 690 V type 2 power circuit
Average impedance	1,5 mOhm 50 Hz 60 A power circuit
Power dissipation per pole	2,4 W AC-3 60 A
Inrush power in VA	200 VA 20 °C 0,75 50 Hz 220 VA 20 °C 0,75 60 Hz 245 VA 20 °C 0,75 50 Hz 245 VA 20 °C 0,75 60 Hz
Hold-in power consumption in VA	20 VA 20 °C 0,3 50 Hz 22 VA 20 °C 0,3 60 Hz 26 VA 20 °C 0,3 50 Hz 26 VA 20 °C 0,3 60 Hz
Operating time	4...19 ms opening 12...26 ms closing
Mechanical durability	6000000 cycles
Operating rate	3600 cyc/h ≤ 60 °C
Minimum switching current	5 mA control circuit
Minimum switching voltage	17 V control circuit
Non-overlap time	1,5 ms on energisation between NC and NO contacts 1,5 ms on de-energisation between NC and NO contacts
Insulation resistance	> 10 MOhm control circuit
Height	132 mm
Width	165 mm
Depth	142 mm
Product weight	2,4 kg

Environment

Standards	CSA C22-2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508
Product certifications	BV CCC CSA DNV (Det Norske Veritas) GL GOST LROS RINA UL
IP degree of protection	IP2x VDE 0106 IP2x IEC 60529
Protective treatment	TH IEC 60068 3
Ambient air temperature for operation	-5...60 °C
Ambient air temperature for storage	-60...80 °C
Permissible ambient air temperature around the device	-40...70 °C at U _c
Operating altitude	3000 m without
Fire resistance	850 °C IEC 60695-2-1
Shock resistance	8 gn contactor opened 10 gn contactor closed
Vibration resistance	2 gn contactor opened 5...300 Hz 4 gn contactor closed 5...300 Hz
Heat dissipation	6...10 W 50/60 Hz control circuit
RoHS EUR conformity date	2Q2009
RoHS EUR status	Will be compliant