

LC2K1210E7

Screw Clamp, 1 NO Aux, Reversing.

Main

| | |
|------------------------|---|
| Action | Reversing |
| Ampere Rating | 12A |
| Approvals | UL Listed File E164862 NLDX2 - CSA Certified File LR43364 Class 3211 04 - IEC Rated 60947 - CE Marked |
| Auxiliary Contacts | 1 N.O. |
| Depth | 2.24 Inches |
| For Use With | AC Control Circuits |
| Height | 2.88 Inches |
| Horsepower Rating | (Single Phase) 0.5HP@115VAC - 1.5HP@230AC (Polyphase) 3HP@200/230VAC - 7.5HP@460VAC - 10HP@575VAC |
| Marketing Trade Name | TeSys |
| Maximum Voltage Rating | 600VAC |
| Mounting Type | Panel |
| Number of Poles | 3-Pole |
| Operating Voltage | 48VAC@50/60Hz |
| Terminal Type | Screw Clamp |
| Type | K-Line |
| Weight | 0.86 Pounds |
| Width | 3.54 Inches |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.