

Main

Action	Non-Reversing
Ampere Rating	6A
Approvals	UL Listed File E164862 NLDX2 - CSA Certified File LR43364 Class 3211 04 - IEC Rated 60947 - CE Marked
Auxiliary Contacts	1 N.C.
Depth	2.24 Inches
For Use With	DC Control Circuits
Height	2.28 Inches
Horsepower Rating	(Single Phase) 0.5HP@115VAC - 1.5HP@230AC (Polyphase) 1.5HP@200/230VAC - 3HP@460/575VAC
Integral Coil Suppression	Yes
Marketing Trade Name	TeSys
Maximum Voltage Rating	600VAC
Mounting Type	Panel
Number of Poles	3-Pole
Operating Voltage	24VDC
Terminal Type	Screw Clamp
Type	K-Line
Weight	0.52 Punds
Width	1.77 Inches

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.