

QO816L100DSCU

QO 100A 8CCT 1PH CU BUS UL LISTED ONLY

Main

Ampere Rating	100A
Application	Designed to meet residential, commercial and industrial requirements to protect electrical systems, equipment and people.
Approvals	UL Listed
Bus Material	Tin Plated Copper
Cover Type	Surface (with door)
Depth	4.00 Inches
Enclosure Rating	NEMA 1
Enclosure Type	Indoor
Grounding Bar	Order separately
Height	9.38 Inches
Main Type	Fixed - Factory installed main lugs
Maximum Single Pole Circuits	16
Maximum Tandem Circuit Breakers	8
Phase	1-Phase
Short Circuit Current Rating	10kA
Spaces	8
Voltage Rating	120/240VAC
Width	4.88 Inches
Wire Size	#8 to 1 AWG(Al/Cu)
Wiring Configuration	3-Wire

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.